

Order Entry via XML

Version 1.0.0

This document was typeset June 20, 2025

Copyright 2005-2022 Accio Data , Inc.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form, or by any means, electronic, mechanical, or otherwise, without the prior consent of Accio Data , Inc.

For information on obtaining permission for use of material from this work, please submit a written request to :

Accio Data , Inc.

PO Box 787

Dripping Springs, TX

78620

For technical support, please contact Accio Data at 512 858-9329.

Errors and omissions : We make every effort to provide you with complete and accurate documentation. If you find errors or omissions in this manual, please report them to us promptly so that we may correct our manuals.

Contents

- 1 Introduction** 7
- 2 Communication** 9
 - 2.1 SNI 9
 - 2.2 Ciphers 9
 - 2.2.1 Protocol 9
 - 2.2.2 Sample Code - Sending XML to Accio Data - C# 11
 - 2.2.3 Sample Code - Sending XML to Accio Data - Visual Basic 13
 - 2.2.4 Sample Code - Sending XML to Accio Data - Ruby 15
- 3 Placing an order** 17
 - 3.1 The Login Block 17
 - 3.2 The Mode Node 17
 - 3.3 The placeOrder Block 18
 - 3.4 The order_on_behalf_of Block 19
 - 3.5 The postBackInfo Block 20
 - 3.5.1 Disable postBackInfo block 21
 - 3.6 The orderInfo Block 22
 - 3.7 The Subject Block 22
 - 3.8 The subOrder Block 24
 - 3.8.1 Address History to 7 Year County Criminal Order XML 27
 - 3.8.2 Address History to 10 Year County Criminal Order XML 27
 - 3.8.3 Address History to 7 Year Statewide Criminal Order XML 27
 - 3.8.4 Address History to 10 Year Statewide Criminal Order XML 28
 - 3.8.5 Address Information Report Order XML 28
 - 3.8.6 Adult Abuse Order XML 28
 - 3.8.7 Adverse Action Process Order XML 28
 - 3.8.8 Consent Based SSN verification with the SSA Order XML 28
 - 3.8.9 Commercial Drivers' License Verification Order XML 28
 - 3.8.10 CDL Employment Verification Order XML 28
 - 3.8.11 Civil County Lower Order XML 29
 - 3.8.12 Civil County Upper Order XML 29
 - 3.8.13 County Criminal Order XML 29
 - 3.8.14 Certified Nurses Aid Registry Order XML 30
 - 3.8.15 Credential Verification Order XML 30
 - 3.8.16 Custom Product Order XML 30
 - 3.8.17 Drug Screen Order XML 31

3.8.18 Education Verification Order XML	31
3.8.19 International Education Verification Order XML	32
3.8.20 Employment Credit Report Order XML	33
3.8.21 Employment Verification Order XML	33
3.8.22 Level2 Employment Verification Order XML	34
3.8.23 Level3 Employment Verification Order XML	35
3.8.24 International Employment Verification Order XML	35
3.8.25 I-9 Order XML	36
3.8.26 EVerify Order XML	37
3.8.27 Evictions Check Order XML	40
3.8.28 FMCSA Crash Inspection Order XML	40
3.8.29 Gap Verification Order XML	40
3.8.30 Medical Sanctions History Order XML (Level 3)	41
3.8.31 Medical Sanctions History Order XML (Level 3 - with verification)	41
3.8.32 Medical Sanctions History Order XML (Level 1)	41
3.8.33 Medical Sanctions History Order XML (Level 1 - with verification)	41
3.8.34 Medical Sanctions History Order XML (Level 1m)	41
3.8.35 Medical Sanctions History Order XML (Level 1m - with verification)	41
3.8.36 Medical Sanctions History Order XML (Level 2)	41
3.8.37 Medical Sanctions History Order XML (Level 2 - with verification)	42
3.8.38 Office of Foreign Assets Control Search	42
3.8.39 Federal Bankruptcy Court Order XML	42
3.8.40 Federal Civil Court Order XML	42
3.8.41 Federal Criminal Court Order XML	42
3.8.42 Federal Statewide Bankruptcy Court Order XML	42
3.8.43 Federal Statewide Civil Court Order XML	42
3.8.44 Federal Criminal Statewide Court Order XML	43
3.8.45 General Sanctions Administration List Check Order XML	43
3.8.46 Global Terrorist Watch List	43
3.8.47 Form I-9 Verification Order XML	43
3.8.48 Mail Completed Report Order XML	43
3.8.49 Monitor National (Multijurisdictional) Criminal Report Order XML	43
3.8.50 MVR Order XML	43
3.8.51 National (Multijurisdictional) Criminal Report Order XML	44
3.8.52 National Federal Criminal Report Order XML	44
3.8.53 National (Multijurisdictional) Criminal with Alias Report Order XML	44
3.8.54 National (Multijurisdictional) Criminal with Alias Report source 2 Order XML	44
3.8.55 Nursing License Order XML	44
3.8.56 Office of Inspector General List Check Order XML	44
3.8.57 Professional Reference Check Order XML	44
3.8.58 International Professional Reference Check Order XML	45
3.8.59 Reference Check Order XML	45
3.8.60 Safety First Order XML	46
3.8.61 Sex Offender Database Order XML	46
3.8.62 Sex Offender Multistate Database Order XML	46
3.8.63 Specially Designated Nationals Database Search Order XML	46
3.8.64 SSN Verification Order XML	46

3.8.65 Standard Credit Report Order XML	46
3.8.66 Statewide Civil Order XML	46
3.8.67 Statewide Criminal Order XML	46
3.8.68 Statewide Criminal Data Base Order XML	47
3.8.69 Trac Order XML	47
3.8.70 Trac_to_7year_criminal Order XML	47
3.8.71 Trac_to_3year_criminal Order XML	47
3.8.72 Trac_to_Federal_criminal Order XML	47
3.8.73 TriMerged Credit Report Order XML	47
3.8.74 Workers Compensation Order XML	47
3.9 The addToOrder Block	47
3.10 Autogenerating Criminal Searches	48
3.11 Order Control Settings	48
3.12 The resultsForwarded Block	52
4 Order Response	53
4.1 Response Error Codes	53
5 Sending Imaged Documents	59
5.1 Image File Formats	59
6 Other XML Queries	61
6.1 Packages	61
6.2 Results for a specific order	61
7 Standard Data Formats	63
7.1 Dates	63
7.2 Data Definition Guide for Common “<placeOrder >” XML Elements	63
7.2.1 Elements of the Subject node	63
7.2.2 Elements of the subOrder node, Education_verification attribute	64
7.2.3 Elements of the subOrder node, Employment_verification attribute	65
7.2.4 Elements of the subOrder node, fmcsa_crash_inspection attribute	66
7.2.5 Elements of the subOrder node, MVR attribute	66
7.3 State Conversion	66

Chapter 1

Introduction

This document is for developers integrating alternate order entry methods into the Accio Data platform. It may be provided to third parties who wish to automatically order from you, or you can use it to develop an alternative web-based ordering platform, to integrate into an applicant tracking system, or similar.

Chapter 2

Communication

2.1 SNI

Communication with Accio Servers requires SNI (Server Name Identification) aware clients. Most modern clients support SNI, but some older software may not.

2.2 Ciphers

Communication with Accio Servers require modern communication ciphers. This may limit the ability of older clients and servers in older environments to connect to the Accio Servers. Some environments like Java 6, Java 7, windows XP, and the like, may not support modern ciphers.

2.2.1 Protocol

Communication with Accio Data is via XML transferred over HTTPS. Documents are posted to the Accio Data server with a Content-Type of text/xml and are returned to you with the same Content-Type.

Files are posted to the URL for the server of the company you're working with. If you're integrating with more than one company using Accio Data's platform, you will interact with each on that company's server URL. XML files are posted to the server at the URL

`https://somecompany.acciodata.com/c/p/researcherxml`



Tip

The URL domain name may be .acciodata.com, .bgsecured.com, or a custom URL.

The XML file sent to Accio Data has the following major components :

- **login** : Your account information

- **mode** : PROD , DRAFT or TEST (defaults to TEST if not specified)
- **placeOrder** : place an order (1 to 50 may be attached)
- **addToOrder** : add to an existing order

2.2.2 Sample Code - Sending XML to Accio Data - C#

This is an example application which can be used to send an XML order over to Accio Data from the command line.

```
using System;
using System.Collections.Generic;
using System.Linq;
using System.Text;

using System.Net;
using System.Web;
using System.IO;

namespace send_xmltoURL
{
    class Program
    {
        static void usage()
        {
            System.Console.WriteLine(
@"
Usage:
send_xmltoURL <server>:[port] <xml file> [url]
<required>, [optional]

example:
send_xmltoURL www.acciodata.com somefile.xml");
        }

        static void Main(string[] args)
        {
            if (args.Length < 2)
            {
                usage();
                return;
            }

            // set up the uri
            string [] hostname = args[0].Split(':');
            string server = hostname[0];
            string port = (hostname.Length > 1) ? hostname[1] : "443";
            string path = (args.Length > 2) ? args[2] : "/c/p/researcherxml";

            // set up a text/xml POST request
            UriBuilder ub = new UriBuilder("https", server, Convert.ToInt16(port), path);
            WebRequest request = WebRequest.Create(ub.Uri);
```

```
request.Method = "POST";
request.ContentType = "text/xml";

// read in the xml file
StreamReader file = File.OpenText(args[1]);
string data = file.ReadToEnd();
file.Close();

Byte[] byte_data = Encoding.UTF8.GetBytes(data);
request.ContentLength = byte_data.Length;

// post the data
Stream data_stream = request.GetRequestStream();
data_stream.Write(byte_data, 0, byte_data.Length);
data_stream.Close();

// get the response.
WebResponse response = request.GetResponse();
Console.WriteLine(((HttpWebResponse)response).StatusDescription);

data_stream = response.GetResponseStream();
StreamReader reader = new StreamReader(data_stream);
string response_string = reader.ReadToEnd();

// display the content.
Console.WriteLine(response_string);

// clean up
reader.Close();
data_stream.Close();
response.Close();
    }
}
}
```

2.2.3 Sample Code - Sending XML to Accio Data - Visual Basic

This is an example application which can be used to send an XML order over to Accio Data from the command line.

Main.vb.txt

```
Imports System
Imports System.Collections.Generic
Imports System.Linq
Imports System.Text

Imports System.Net
Imports System.Web
Imports System.IO

Module Accio_vb_sample

    Sub usage()
        System.Console.WriteLine(vbCr & vbLf & "Usage:  " & vbCr & vbLf &
            "  send_xmltoURL <server>:[port] <xml file> [url]" & vbCr & vbLf &
            "  <required>, [optional] " & vbCr & vbLf & "    " & vbCr & vbLf &
            "example:" & vbCr & vbLf & "  send_xmltoURL www.acciodata.com somefile.xml")
    End Sub

    Sub Main(ByVal args As String())
        If args.Length < 2 Then
            usage()
            Return
        End If

        ' set up the uri
        Dim hostname As String() = args(0).Split(":")
        Dim server As String = hostname(0)
        Dim port As String = If((hostname.Length > 1), hostname(1), "443")
        Dim path As String = If((args.Length > 2), args(2), "/c/p/researcherxml")

        ' set up a text/xml POST request
        Dim ub As New UriBuilder("https", server, Convert.ToInt16(port), path)
        Dim request As WebRequest = WebRequest.Create(ub.Uri)
        request.Method = "POST"
        request.ContentType = "text/xml"

        ' read in the xml file
        Dim xml_file As StreamReader = File.OpenText(args(1))
        Dim data As String = xml_file.ReadToEnd()
        xml_file.Close()
    End Sub
End Module
```

```
Dim byte_data As [Byte]() = Encoding.UTF8.GetBytes(data)
request.ContentLength = byte_data.Length

' post the data
Dim data_stream As Stream = request.GetRequestStream()
data_stream.Write(byte_data, 0, byte_data.Length)
data_stream.Close()

' get the response.
Dim response As WebResponse = request.GetResponse()
Console.WriteLine(DirectCast(response, HttpWebResponse).StatusDescription)

data_stream = response.GetResponseStream()
Dim reader As New StreamReader(data_stream)
Dim response_string As String = reader.ReadToEnd()

' display the content.
Console.WriteLine(response_string)

' clean up
reader.Close()
data_stream.Close()
response.Close()
End Sub

End Module
```

2.2.4 Sample Code - Sending XML to Accio Data - Ruby

This is an example application which can be used to send an XML order over to Accio Data from the command line.

```
#!/usr/local/bin/ruby

USAGE = <<txt
  Usage:
    send_xmltoURL <server>:[port] <xml file> [postpath]

    <required>, [optional]

  example:
    send_xmltoURL orders.someplace.com somefile.xml
txt

def main()

  if(ARGV[0].to_s.empty? && ARGV[1].to_s.empty?)
    puts USAGE
    exit(1)
  end

  servername,port = ARGV[0].split(':')
  (port==nil) && port = 443
  xmlfilename = ARGV[1]
  postpath = ARGV[2]
  (postpath.to_s.length ==0) && (postpath = '/c/p/researcherxml')
  headers = {'Content-Type'=> 'text/xml'}

  require "cgi"
  require 'net/https'

  postdoc = File.read(xmlfilename) # read in XML file

  h = Net::HTTP.new(servername, port)
  h.use_ssl=true
  h.request_post(postpath, postdoc, headers) {|response|
    STDOUT.print(response.body) # show the response
  }
end

main()
```


Chapter 3

Placing an order

To place an order, the XML file you send to Accio Data will contain one root node named `New_Order` containing two subnode types :

- **login** : Your account information
- **mode** : PROD—DRAFT—TEST
- **placeOrder** : an order (more than one may be attached)

3.1 The Login Block

```
<login>
  <account>accountname</account>
  <username>username</username>
  <password>yourpassword</password>
</login>
```

This block is required for all requests. The account, username, and password will be assigned to you by the company you're working with following their administration guide's instructions in the "Setting up Vendor (Researcher) Accounts" section.

3.2 The Mode Node

```
<mode>PROD</mode>
```

Mode defaults to TEST, valid values are TEST, DRAFT, or PROD. Transactions submitted in TEST mode go through the same validation as production mode posts, and return the same XML response document as PROD posts — order numbers and all. However, in TEST mode the orders are not committed.

DRAFT mode orders will return XML to you the same as TEST or PROD mode, but like TEST mode orders will not be dispatched to suppliers. Unlike test mode, the order will show up in the system in draft mode. TEST mode orders don't show up except via *Screenings / Look Up Orders* — if you have the order number — and can be committed and become production orders, or deleted through the Accio UI.

When writing an integration, orders should be placed in TEST mode while testing your XML interface. Once you're done with initial testing, move to DRAFT mode. Draft mode orders will persist on the remote system, allowing you to log in via the web interface and review the order to ensure that the XML you sent created the intended order.

Before posting PROD mode orders, you should coordinate with your screening services provider to ensure that orders are appropriately discarded or processed as production orders.

3.3 The placeOrder Block

```

<placeOrder number='123'>  number is optional, up to 256 characters. Quoted back
                             with results where used
  <account>accountname</account>  Optional, used if placing orders on behalf of
  <username>username</username>   user, however order_on_behalf_of is preferred
  <profile>profile</profile>     Optional, a profile string
  <order_on_behalf_of/>          Optional block, identifies the ordering account and user
  <postBackInfo/>               Optional block, info on where to post back status and results
  <orderInfo/>                  Optional block, info on person requesting the order
  <subject>...</subject>        exactly one subject per placeOrder
  <package> A La Carte</package> Optional, defaults to A La Carte
  <subOrder type='County_criminal'> ... </subOrder> any number >=1 may be included
  <image/> zero to many images per order
  <GenerateCrimFromSubjectAddresses/>      Optional autocrim, follow link for info
  <Cancel_out_of_scope_elements/>         Optional, follow link for info
  <UseOrderingRequirements/>             Optional, follow link for info
  <Upgrade_products_per_package/>        Optional, follow link for info
  <Delete_disallowed_products/>         Optional, follow link for info
  <Add_AKAs_from_AIM/>                  Optional, follow link for info
  <Expand_AKAs_to_Suborders/>           Optional, follow link for info
  <IncludeDefaultProducts/>            Optional, follow link for info
  <IncludePreselectedProducts/>       Optional, follow link for info
  <preselect_all_included_products/>    Optional, Draft mode only, follow link for info
  <SuppressApplicantPortalEmail/>      Optional, follow link for info
  <SuppressDraftEmailNotice/>         Optional, Draft mode only, follow link for info
  <SendApplicantInviteViaBoth/>       Optional, follow link for info
  <SendApplicantInviteViaSMS/>       Optional, follow link for info
  <SendApplicantInviteViaEMail/>     Optional, follow link for info
  <resultsForwarded>...</resultsForwarded>  Optional, follow link for info

</placeOrder>

```

When placing orders on behalf of another user, the system checks to make sure the user specified in the Login Block has permission to place orders on the users behalf. If the user specified in the Login Block does not have permission, the following error is generated

```

<errortext>
a placeOrder/addToOrder is attempting to place the order on
behalf of another user, but this account does not have sysop or parent privileges

```

</errortext>

When sending in orders, we recommend sending one order per XML post. This makes the debugging process easier if errors occur, and it also makes it easier to identify and separate out any bad orders.

If you do send more than one order per post, orders will be processed in document order until all have been processed or the first error is found. Your confirmation XML document will confirm all placed orders and, if an error occurred, will indicate the type of error in an <error> XML node.

Because the parser stops processing at the first error, you will never receive more than one error message in a response document.

If using the number attribute on the placeOrder node, the number supplied must be an integer. This number will not be quoted back in the placeOrder response, but it will be quoted back in any results that are posted to your server in the <completeOrder> node as follows :

```
<completeOrder number='123' remote_number='555444' ...>
```

number is the number that you supplied when placing the order, and remote_number is the order number assigned in the remote system and quoted to you in the placeOrder response.

The profile is not used internally by Accio, but can be used by those vendors receiving Accio xml however they see fit. When generating outbound Accio XML this value can be set on site setup under Vendor Configuration → Accio Integrated using the <Vendor Name> Profile field. You can also reach this setting from the vendor configuration page using the System Level variables gear icon at the bottom of the page.

NOTE This is intended to be used by third party vendors as they see fit. Set this value as directed by the third party vendor.

3.4 The order_on_behalf_of Block

The placeOrder's order_on_behalf_of node may contain account and username nodes (both) or a match_by_field node. All three are allowed in which case account and username override match_by_field. If account is present username must also be present.

The following values for match_by_field fieldname may be used:

- primaryuser_contact_email
- primaryuser_contact_name
- primaryuser_contact_title
- primaryuser_contact_telephone
- primaryuser_contact_fax

The matching text must be a complete match (not a partial match or a wildcard match) that identifies an account and user. Note that some values may identify more than one user in which case if the matches are all in the same account then the first match will be used, however if the list includes matches from more than one account an error response will be returned.

An account and username may also be present at the placeOrder or addToOrder level and will be supported for backward compatibility, however order_on_behalf_of is preferred. If account and username are only supplied in the login node then the login user is the ordering user.

```

<order_on_behalf_of>   Optional, preferred way to supply ordering account and username
  <account>someAccount</account>   Optional, ordering account text
  <username>someUserName</username>   Optional, ordering user text
  <match_by_field fieldname="someFieldName">someMatchFieldText</match_by_field>
    Optional, used to match a user by criteria from the account record
</order_on_behalf_of>

```

3.5 The postBackInfo Block

The placeOrder's postBackInfo node is an optional block which contains information on where to post back XML status and results of the order. It also contains what type of status and results to post back.

All allowable postBackInfo nodes are shown in the example below.

```

<postBackInfo>
  <authentication>   HTTP authorization Info
    <type>Basic</type>   The type of authentication, 'Basic' or 'Token'
    <username>authuser</username>   The username to use in the auth header for 'Basic',
    or the header name for 'Token'
    <password>authpassword</password>   The password to use in the auth header for 'Basic,
    or the token for 'Token'

  </authentication>
  <URL>https://somedomainname/somepath/someprogram</URL>   exactly one URL per postBackInfo
  <guID>styue786tghYTR4567</guID>   exactly one guID per postBackInfo
  <account>someAccount</account>   Optional, account text
  <username>someUserName</username>   Optional, username text
  <request_source>someATSName</request_source>   Optional, text letters and numbers only
  <postback_types>ICR::OCR</postback_types>   Optional, see definition
</postBackInfo>

```

Note: The password in the authentication block is XML encoded. The &, <, >, ", and ' characters will be encoded with & < > "e; and '. These characters must be decoded if compared to the unencoded password.

If the postBackInfo node is supplied, it must contain one URL node and one guID node both with values. The URL node must contain the full URL to where to post back order status and results XML. The guID node contains the text which will be placed in the account, username, and password nodes of the status and results XML posts to the URL.

- If the account node is available and has a value, this value, instead of the guID value, will be used in the account node of the status and results XML posts the URL.
- If the username node is available and has a value, this value, instead of the guID value, will be used in the username node of the status and results XML posts the URL.
- The value used in request_source node is used to tell which service is placing the order.

The postback_types node is used to define the type of status and results post backs to send to the URL. If this node is not available the default is to send all status and result XML post backs to the URL. One or more of the following types may be used separated by 2 colons "::".

Type Code	Post Back XML
IPV	Send the in progress vendor status XML when the order goes from DRAFT to an actual order in the system.
ICR	Send component completion XML when each component of the order completes.
OCR	Send complete order XML when the order completes.
IPC	Send waiting for applicant status XML when the order is placed through the invitation.
EXP	Send invitation expired notification when a candidate invitation expires.
IPR	Send waiting for recruiter status XML when the order is placed through the invitation and completed in a draft mode waiting for the recruiter to complete.
CNF	Send the in-progress vendor status XML when the order goes from an invitation being completed by the applicant or completed by the recruiter when the order is placed through the invitation and completed in a draft mode.
DEL	Sent if the order is deleted or canceled. Note: This is for the order, not an individual component.
PDF	Send a pdf of the completed report and no other other information back when the order is complete.
PDI	Include a pdf along with XML order details of the completed report back when the order is complete.
RDC	Send a post back every time the report disposition changed.
CETA	Send component level ETA updates.
NONE	Use this, by itself, if for some reason you are sending a post back block and don't want post backs.

If the receiving end requires the use of HTTP Basic Authorization, the credentials to use may be passed in the “authorization” block inside the “postBackInfo” block. This block contains the following nodes.

Node	Contents Description
type	The type of HTTP authorization header to send, currently only “Basic” and “Token” are supported.
username	The user name to be sent in the HTTP Basic Authorization header.
password	The password to be sent in the HTTP Basic Authorization header.

3.5.1 Disable postBackInfo block

The system can be configured to ignore the contents of the postBackInfo block. Setting the “Ignore Postback Info Block” system variable at the site, price book, account, or package level to “Yes” will result in the system ignoring the postBackInfo block as if it has not been included in the XML.

3.6 The orderInfo Block

The placeOrder's orderInfo node contains miscellaneous information about the order such as information about the person requesting the order. Many of these miscellaneous items can have default settings on the Accio Data server, and where they do setting the use_default attribute to Y will instruct us to pull the default information from our database. use_default setting is only applied if no value is specified for the element. If a value is specified it will be honored. Not specifying use_default or a value for the element will result in empty nodes in the order for these fields.

All allowable orderInfo nodes are shown in the example below. use_default is indicated for the nodes that support this feature.

<orderInfo>	Optional block, info on person requesting the order
<requester_name use_default='Y' />	Optional, 50 characters, name of person ordering
<requester_phone use_default='Y' />	Optional, 50 characters, phone of person ordering
<requester_fax use_default='Y' />	Optional, 50 characters, fax of person ordering
<requester_email use_default='Y' />	Optional, one address or a colon separated list
<requester_billingdata />	Optional, 128 characters, free format, will appear on invoices
<requester_billingdata2 />	Optional, 128 characters, free format
<requester_billingdata3 />	Optional, 128 characters, free format
<requester_billingdata4 />	Optional, 128 characters, free format
<requester_billingdata5 />	Optional, 128 characters, free format
<requester_billingdata6 />	Optional, 128 characters, free format
<requester_billingdata7 />	Optional, 128 characters, free format
<requester_billingdata8 />	Optional, 128 characters, free format
<requester_billingdata9 />	Optional, 128 characters, free format
<requester_billingdata10 />	Optional, 128 characters, free format
</orderInfo>	

3.7 The Subject Block

The subject block contains identifying information on the subject of this order. An example subject block with all possible subject data fields follows:

<subject>	
<name_first>John</name_first>	letters, dashes, and apostrophes only
<name_middle>Q</name_middle>	letters, dashes, and apostrophes only
<name_last>Smith</name_last>	letters, dashes, and apostrophes only
<has_no_middle_name>U</has_no_middle_name>	Y, N or U only
<name_type>Current</name_type>	Current, Previous, Maiden, or Alias only
<name_suffix>IV</name_suffix>	free form
<name_lastmaiden>William</name_lastmaiden>	optional, letters, dashes, and apostrophes only
<name_mother_maiden>Doe</name_mother_maiden>	optional, letters, dashes, and apostrophes only
<name_complete_mother>Jane Smith</name_complete_mother>	optional, free form
<name_complete_father>John Smith</name_complete_father>	optional, free form
<alias>	zero to 10 aliases may be specified
<name_first>James</name_first>	letters, dashes, and apostrophes only
<name_middle></name_middle>	letters, dashes, and apostrophes only
<name_last>Smith</name_last>	letters, dashes, and apostrophes only

<name_suffix></name_suffix>	free form
<has_no_middle_name>U</has_no_middle_name>	Y, N or U only
<name_type>Current</name_type>	Current, Previous, Maiden, or Alias only
</alias>	
<ssn>112111234</ssn>	no separators, integer (short #s left zero filled)
<country>USA</country>	Optional. should be blank or USA for US addresses. ISO 3166-1 Alpha-3 codes preferred; Max 256 chars
<address>123 Main Street</address>	
<city>Austin</city>	
<state>TX</state>	See 'State Conversion'
<jobstate>CA</jobstate>	See 'State Conversion'
<jobcity>Sacramento</jobcity>	
<jobzip>94203</jobzip>	
<jobtitle>Office Worker</jobtitle>	
<zip>78731</zip>	
<FCRAPurpose>Employment by Hire or Contract</FCRAPurpose>	Contact your screener for a list
<prioraddress>	Optional, zero to many can be listed
	Shows as Candidate Supplied Addr. Hist. on report
<from>19990512</from>	Must be YYYYMMDD
<to>20020113</to>	Must be YYYYMMDD
<address>123 Main Street</address>	
<city>Austin</city>	
<state>TX</state>	
<county>Travis</county>	optional
<zip>78731</zip>	
</prioraddress>	
<dob>19740301</dob>	YYYYMMDD. Unknown portions may be zeroed. E.G. 19740300 if day is unknown.
	optional
<email>jane.doe@noemail.com</email>	
<race>U</race>	U-unknown A-Asian B-Black H-Hispanic I-Indian
<gender>M</gender>	M, F, U, or blank
<dlnum>0123456789</dlnum>	optional
<dlcountry>USA</dlcountry>	optional, ISO 3166-1 Alpha-3 codes preferred; Max 50 chars
<dlstate>NJ</dlstate>	optional, 2 char USA state. See 'State Conversion'
<intlstate>Ontario</intlstate>	optional, non-USA state/province
<citizenship_status>Citizen</citizenship_status>	Needed for EVerify: Citizen Lawful Permanent Resident Noncitizen Authorized To Work not required - for client use as desired
<employment_status/>	
<phone_number>555-555-1212</phone_number>	may not be present
<has_admitted_convictions/>	Y N. Default's to 'D' if not selected
<admitted_conviction_details/>	Should only be present if Y above
<manager_notes_title>	optional
<manager_notes>	optional
<client_notes/>	Notes entered by the client. free-form, no char limit

<code><client_disposition/></code>	Disposition entered by the client (Report disposition) free-form, 128 characters max
<code><ApplicantID/></code>	Optional. for customer use. Max 128 characters
<code><piifromapplicant/></code>	optional if Y send email to collect PII
<code><portalfromapplicant/></code>	optional if Y send to applicant to complete
<code><require_ews/></code>	optional if Y require electronic signature
<code><applicantdocupload/></code>	optional if Y send to applicant to upload required documents if any
<code><RequisitionNumber/></code>	Optional. for customer use. Max 32 characters
<code><subjectRequestsReportCopy/></code>	Optional. If Y, send email to applicant when complete
<code><quoteback_1>WSDF347865RR</quoteback_1></code>	optional quote back
<code><quoteback_2>1239876540</quoteback_2></code>	optional quote back
<code><quoteback_3>YY7654902736TTT</quoteback_3></code>	optional quote back
<code><intlgovtid/></code>	Optional - NON-US Government ID number
<code><intlgovtid_descr/></code>	Description of above
<code><country_of_birth/></code>	Optional. ISO 3166-1 Alpha-3 codes preferred; Max 256 chars
<code><state_of_birth/></code>	Optional. Max 256 characters
<code><city_of_birth/></code>	Optional. Max 128 characters
<code><applicant_pays/></code>	Optional. If Y, applicant pays for the order
<code><rent_monthly/></code>	Optional
<code><income_monthly/></code>	Optional

`</subject>`

NOTE Although the 'require_ews' is optional, the system will set it to 'Y' if the node is missing and either the 'piifromapplicant' or 'portalfromapplicant' are set to 'Y'. You will need to explicitly set 'require_ews' to 'N' in order to disable the Release Form when also requesting 'piifromapplicant' or 'portalfromapplicant'.

3.8 The subOrder Block

The subOrder's type dictates the subnodes of the subOrder block.

```
<subOrder type='County_criminal'>
  ...
  subOrder type-specific xml nodes
  ...
</subOrder>
</placeOrder>
```



Tip

NOTE: It is possible to provide a "number" attribute for a subOrder for orders in PROD mode. The order must also not use `<portalfromapplicant>`. If the order is sent in DRAFT mode or using `<portalfromapplicant>`, the number will not be maintained as the subOrders are subject to change.

Valid subOrder types have a link to sample XML and are as follows :

- [add2crim7yr](#) – Address history to seven year county criminal history
- [add2crim10yr](#) – Address history to ten year county criminal history
- [add2statewidecrim7yr](#) – Address history to seven year statewide criminal history
- [add2statewidecrim10yr](#) – Address history to ten year statewide criminal history
- [Adult_Abuse](#) – Adult Abuse Registry Search
- [adverse_action_process](#) – Adverse Action Process
- [AIM](#) – Address History Search
- [AIM2](#) – Address History Search second Source
- [CBSV](#) – Consent Based SSN verification with the SSA
- [CDL_Employment_verification](#) – Commercial Drivers' license employment verification
- [CDLIS](#) – Commercial Drivers' license verification
- [Civil_County_criminal_lower](#) – Lower Civil county court search (nothing to do with criminal, misnomer)
- [Civil_County_criminal_upper](#) – Upper Civil county court search (nothing to do with criminal, misnomer)
- [County_criminal](#) – County criminal courthouse search
- [cna_registry](#) – Certified nurses aid registry search
- [Credential_verification](#) – Professional License or credentials verification
- [Credit](#) – Employment Credit Report
- [Credit_std](#) – Standard Credit Report
- [Credit_tri](#) – TriMerged Credit Report
- [cp_customproductcode](#) – Custom Product
- [Drug_screen](#) – Drug screen
- [Drug_Alcohol_screen](#) – (not supported) Drug and alcohol screen
- [Drug_schedule](#) – (not supported) Online scheduled drug screen
- [Education_verification](#) – Education verification
- [Employment_verification](#) – Employment verification
- [Everify](#) – Electronically verify the employment eligibility of newly hired employees
- [evictions_check](#) – Check eviction history
- [FACIS_L1](#) – Medical Sanctions History Level 1
- [FACIS_L2](#) – Medical Sanctions History Level 2
- [FACIS](#) – Medical Sanctions History Level 3
- [FACIS_L1M](#) – Medical Sanctions History Level 1m
- [FACIS_L1MV](#) – Medical Sanctions History Level 1m (w/verification)
- [FACIS_L1_WLV](#) – Medical Sanctions History Level 1 (w/ license verification)
- [FACIS_L2_WLV](#) – Medical Sanctions History Level 2 (w/ license verification)
- [FACIS_L3_WLV](#) – Medical Sanctions History Level 3 (w/ license verification)
- [FACIS_L1V](#) – Medical Sanctions History Level 1 (w/verification)
- [FACIS_L2V](#) – Medical Sanctions History Level 2 (w/verification)
- [FACIS_L3V](#) – Medical Sanctions History Level 3 (w/verification)

- **FACIS_L1V_WLV** – Medical Sanctions History Level 1 (w/verification and license verification)
- **FACIS_L2V_WLV** – Medical Sanctions History Level 2 (w/verification and license verification)
- **FACIS_L3V_WLV** – Medical Sanctions History Level 3 (w/verification and license verification)
- **FACIS_ALIAS_L1** – Medical Sanctions History Alias Level 1
- **FACIS_ALIAS_L2** – Medical Sanctions History Alias Level 2
- **FACIS_ALIAS** – Medical Sanctions History Alias Level 3
- **FACIS_ALIAS_L1_WLV** – Medical Sanctions History Alias Level 1 (w/ license verification)
- **FACIS_ALIAS_L2_WLV** – Medical Sanctions History Alias Level 2 (w/ license verification)
- **FACIS_ALIAS_L3_WLV** – Medical Sanctions History Alias Level 3 (w/ license verification)
- **FACIS_ALIAS_L1V** – Medical Sanctions History Alias Level 1 (w/verification)
- **FACIS_ALIAS_L2V** – Medical Sanctions History Alias Level 2 (w/verification)
- **FACIS_ALIAS_L3V** – Medical Sanctions History Alias Level 3 (w/verification)
- **FACIS_ALIAS_L1V_WLV** – Medical Sanctions History Alias Level 1 (w/verification and license verification)
- **FACIS_ALIAS_L2V_WLV** – Medical Sanctions History Alias Level 2 (w/verification and license verification)
- **FACIS_ALIAS_L3V_WLV** – Medical Sanctions History Alias Level 3 (w/verification and license verification)
- **FACIS_L1_2** – Medical Sanctions History Level 1 2
- **FACIS_L2_2** – Medical Sanctions History Level 2 2
- **FACIS_2** – Medical Sanctions History Level 3 2
- **FACIS_L1V_2** – Medical Sanctions History Level 1 (w/verification) 2
- **FACIS_L2V_2** – Medical Sanctions History Level 2 (w/verification) 2
- **FACIS_L1M_2** – Medical Sanctions History Level 1m 2
- **FACIS_L1MV_2** – Medical Sanctions History Level 1m (w/verification) 2
- **FACIS_L3V_2** – Medical Sanctions History Level 3 (w/verification) 2
- **OFAC** – Office of Foreign Assets Control search)
- **Federal_criminal_bankruptcy** – Federal bankruptcy court search (nothing to do with criminal, misnomer)
- **Federal_criminal_civil** – Federal civil courthouse search (nothing to do with criminal, misnomer)
- **Federal_criminal_criminal** – Federal criminal courthouse search
- **Federal_statewide_bankruptcy** – Federal Statewide bankruptcy court search
- **Federal_statewide_civil** – Federal Statewide civil courthouse search
- **Federal_statewide_criminal** – Federal Statewide criminal courthouse search
- **fmcsa_crash_inspection** – Federal Motor Carrier Safety Administration Crash Inspection Report
- **GAP** – Employment gap verification
- **globalreport** – Terrorist watch list search
- **GSA** – General Sanctions Administration list check
- **i9verification** – Form I-9 verification

- **International_Education_verification** – International Education verification
- **International_Employment_verification** – International Employment verification
- **Level2_Employment_verification** – Level2 Employment verification
- **Level3_Employment_verification** – Level3 Employment verification
- **mail_completereport** – Mail completed report
- **Metro_County_criminal** – (not supported) Metro county criminal search
- **monitor_national_criminal** – Recurring multijurisdictional criminal search. **Note:** this product must be ordered with an order that also includes a USOneSearch or USALiasSearch
- **MVR** – Drivers' license history
- **National_Criminal** – National/multistate criminal database search
- **National_Criminal2** – National/multistate criminal database search second Source
- **National_Federal_Criminal** – National federal criminal database search
- **National Alias Criminal** – National/multistate criminal with alias database search
- **National Alias Criminal2** – National/multistate criminal with alias database search second Source
- **nursing_license** – Nursing license check
- **OIG** – Office of Inspector General list check
- **Professional_Reference_check** – Call a person and check a reference
- **Reference_check** – Call a person and check a reference
- **safety1st** – Appriss product for organizations that does an AIM and criminal background check
- **SDN** – Specially Designated Nationals database search
- **Sex_Offender** – Statewide Sex offender search. Could be a database or a repository search
- **sex_offender_nationwide** – Multistate sex offender database
- **SSN** – SSN verification. E.G. is it validly issued, when & where, and is there a death record associated with it?
- **Statewide_civil** – Statewide civil repository search
- **Statewide_criminal** – Statewide criminal repository search
- **Statewide_criminal_db** – Statewide criminal database search
- **Trac** – Credit based address history (credit header)
- **Trac_to_7year_criminal** – Credit header pulled, 7 year criminal history searched, credit header and criminal history bundled and returned.
- **Trac_to_3year_criminal** – As above with 3 year history
- **Trac_to_Federal_criminal** – 7 year address history to Federal district criminal search
- **USMA_retail_theft_screen** – (not supported) history
- **Workers Compensation** – Workers' compensation history search (single state)

3.8.1 Address History to 7 Year County Criminal Order XML

```
<subOrder type='add2crim7yr'>
</subOrder>
```

3.8.2 Address History to 10 Year County Criminal Order XML

```
<subOrder type='add2crim10yr'>
</subOrder>
```

3.8.3 Address History to 7 Year Statewide Criminal Order XML

```
<subOrder type='add2statewidecrim7yr'>
</subOrder>
```

3.8.4 Address History to 10 Year Statewide Criminal Order XML

```
<subOrder type='add2statewidecrim10yr'>
</subOrder>
```

3.8.5 Address Information Report Order XML

```
<subOrder type='AIM'>
</subOrder>
```

```
<subOrder type='AIM2'>
</subOrder>
```

3.8.6 Adult Abuse Order XML

```
<subOrder type='Adult_Abuse'>
  <state>TX</state>
</subOrder>
```

3.8.7 Adverse Action Process Order XML

```
<subOrder type='adverse_action_process'>
</subOrder>
```

3.8.8 Consent Based SSN verification with the SSA Order XML

```
<subOrder type='CBSV'>
</subOrder>
```

3.8.9 Commercial Drivers' License Verification Order XML

```
<subOrder type='CDLIS'>
</subOrder>
```

3.8.10 CDL Employment Verification Order XML

```
<subOrder type='CDL_Employment_verification'>
  <company_name>ABCCO</company_name>
  <position>TEST ASSISTANT</position>
  <contact>JOHN SHARP</contact>
  <email>john@acme.com</email>
  <phone_number>555-555-1212</phone_number>
  <phone_extension>123</phone_extension>
  <start_date>20000101</start_date>           Must be YYYYMMDD
  <end_date>20020101</end_date>             Must be YYYYMMDD
  <income>111.00</income>
  <income_type>hourly</income_type>         hourly, weekly, monthly, semimonthly,
                                             biweekly, annually
  <reason_for_leaving>this is an optional field</reason_for_leaving>
  <isdot/>                                   Y|N - optional, defaults to N if omitted
  <address1>123 main street</address1>
  <address2></address2>
```

```

<city>AUSTIN</city>
<state>TX</state>
<zip>78731</zip>
<comments>Some kind of comment optional</comments>
<question>
  <prompt>Test Question 1</prompt>
  <standardresponse>Pass</standardresponse>
  <standardresponse>Fail</standardresponse>
</question>
<question>
  <prompt>Test Question 2</prompt>
  <standardresponse>Yes</standardresponse>
  <standardresponse>No</standardresponse>
</question>
<salarykey>1234</salarykey>
</subOrder>

```

See 'State Conversion'

3.8.11 Civil County Lower Order XML

```

<subOrder type='Civil_County_criminal_lower'>
  <county>Travis</county>
  <state>TX</state>
  <years_conviction>7</years_conviction>
  <years_nonconviction>7</years_nonconviction>
  <notes_to_supplier>Please search</notes_to_supplier>
</subOrder>

```

optional
optional
optional,
free-form,
65000 char limit

3.8.12 Civil County Upper Order XML

```

<subOrder type='Civil_County_criminal_upper'>
  <county>Travis</county>
  <state>TX</state>
  <years_conviction>7</years_conviction>
  <years_nonconviction>7</years_nonconviction>
  <notes_to_supplier>Please search</notes_to_supplier>
</subOrder>

```

optional
optional
optional,
free-form,
65000 char limit

3.8.13 County Criminal Order XML

```

<subOrder type='County_criminal'>
  <county>Travis</county>
  <state>TX</state>
  <years_conviction>7</years_conviction> optional
  <years_nonconviction>7</years_nonconviction> optional
  <searchtype>both</searchtype> one of: felony, misdemeanor, both
  <notes_to_supplier>Please search</notes_to_supplier> optional,
  free-form,
  65000 char limit
</subOrder>

```

3.8.14 Certified Nurses Aid Registry Order XML

```

<subOrder type='cna_registry'>
  <state>TX</state>
  <notes_to_supplier>Provide Docket Copies for Felonies</notes_to_supplier> optional,
  free-form,
  65000 char limit
</subOrder>

```

3.8.15 Credential Verification Order XML

```

<subOrder type='Credential_verification'>
  <description>CPA</description>
  <state>TX</state> optional. See 'State Conversion'
  <organization_name>CPAs of Texas</organization_name>
  <license_number>CPA1234</license_number>
  <date_received>20010201</date_received> Must be YYYYMMDD
  <expiration_date>20110201</expiration_date> Must be YYYYMMDD
  <comments>Some kind of comment optional</comments>
  <question>
    <prompt>Test Question 1</prompt>
    <standardresponse>Pass</standardresponse>
    <standardresponse>Fail</standardresponse>
  </question>
  <question>
    <prompt>Test Question 2</prompt>
    <standardresponse>Yes</standardresponse>
    <standardresponse>No</standardresponse>
  </question>
</subOrder>

```

3.8.16 Custom Product Order XML

```

<subOrder type='cp_customproductcode'> customproductcode is configurable by the Accio client
  <address>123 Main Street</address> optional
  <city>Austin</city> optional
  <country>USA</country> optional ISO 3166-1 Alpha-3 codes preferred; Max 256 chars
  <county>Travis</county> optional
  <dlnum>99990000</dlnum> optional
  <end_date>20100101</end_date> optional Must be YYYYMMDD

```

```

<intlgoovtid>99990000</intlgoovtid> optional
<intlgoovtid_descr>Identity Card</intlgoovtid_descr> optional
<island>Bora Bora</island> optional
<license_issuer>TX</license_issuer> optional
<license_number>99990000</license_number> optional
<roll_number>999AAA00</roll_number> optional
<searchdescription>Text field</searchdescription> optional
<state>TX</state> optional
<start_date>20000101</start_date>optional Must be YYYYMMDD
<tax_id_number>12345</tax_id_number> optional
<chain_of_custody>0103350542</chain_of_custody> optional
<specimen_collection_date>2008-04-16 Em:pt</specimen_collection_date> optional
<donorId>275969105</donorId> optional
<specimenId>3787652Y</specimenId> optional
<sampleType>urine</sampleType> optional
<DOT>N</DOT> optional Y|N
<examination_date>20100101</examination_date> optional Must be YYYYMMDD
<physicalId>153245</physicalId> optional
</subOrder>

```

3.8.17 Drug Screen Order XML

```

<subOrder type='Drug_screen'>
  <chain_of_custody>0103350542</chain_of_custody>
  <specimen_collection_date>2008-04-16 Em:pt</specimen_collection_date>
  <donorId>275969105</donorId>
  <specimenId>3787652Y</specimenId>
  <sampleType>urine</sampleType>
  <DOT>N</DOT> Y|N
</subOrder>

```

3.8.18 Education Verification Order XML

```

<subOrder type='Education_verification'>
  <school_name>Johns Hopkins</school_name>
  <campus>Berkeley Teaching Hospital</campus>
  <major>Orthopedic resident</major>
  <degree>M.D.</degree>
  <name_first>Sarah</name_first>
  <name_last>Smith</name_last>
  <GPA></GPA>
  <student_id_number></student_id_number>
  <address1></address1>
  <address2></address2>
  <city></city>
  <state></state> See 'State Conversion'
  <zip></zip>
  <country></country> Not required, normally blank.
  If the value is not blank or "USA", this product is converted to
  International Education/Employment (when it's available in the package)

```

```

    ISO 3166-1 Alpha-3 codes preferred; Max 128 chars
<attended_from>19990512</attended_from>Must be YYYYMMDD
<attended_to>20060513</attended_to>    Must be YYYYMMDD
<transcript>N</transcript>    Y|N
<graduated>Y</graduated>    Y|N
<highest_achieved>Y</highest_achieved>    Y|N
<currently_enrolled>Y</currently_enrolled>    Y|N
<graduation_date></graduation_date>
<phone>555-555-1212</phone>
<levelCompleted/>    restricted use
<question>
  <prompt>Test Question 1</prompt>
  <standardresponse>Pass</standardresponse>
  <standardresponse>Fail</standardresponse>
</question>
<question>
  <prompt>Test Question 2</prompt>
  <standardresponse>Yes</standardresponse>
  <standardresponse>No</standardresponse>
</question>
  <comments>Some kind of comment optional</comments>
</subOrder>

```

3.8.19 International Education Verification Order XML

```

<subOrder type='International_Education_verification'>
  <school_name>Oxford Business College</school_name>
  <major>Business Administration</major>
  <degree>MBA</degree>
  <GPA></GPA>
  <name_last>Accio</name_last>
  <name_first>Joe</name_first>
  <highest_achieved></highest_achieved>
  <currently_enrolled>Y</currently_enrolled>
  <student_id_number></student_id_number>
  <address1>65 George Street</address1>
  <address2></address2>
  <city>Oxford</city>
  <state>Oxford</state>
  <intlzip>OX1 2BQ</intlzip>
  <country>UK</country> ISO 3166-1 Alpha-3 codes preferred; Max 128 chars
  <attended_from>19990512</attended_from>Must be YYYYMMDD
  <attended_to>20060513</attended_to>    Must be YYYYMMDD
  <transcript>N</transcript>    Y|N
  <graduated>Y</graduated>    Y|N
  <graduation_date></graduation_date>
  <phone>+33 1 49 60 19 60</phone>
  <levelCompleted/>    restricted use

```

```

<roll_number/> may be required for some countries
<comments>Some kind of comment optional</comments>
<question>
  <prompt>Test Question 1</prompt>
  <standardresponse>Pass</standardresponse>
  <standardresponse>Fail</standardresponse>
</question>
<question>
  <prompt>Test Question 2</prompt>
  <standardresponse>Yes</standardresponse>
  <standardresponse>No</standardresponse>
</question>
</subOrder>

```

3.8.20 Employment Credit Report Order XML

```

<subOrder type='Credit'>
</subOrder>

```

3.8.21 Employment Verification Order XML

```

<subOrder type='Employment_verification'>
  <company_name>ABCCO</company_name>
  <position>TEST ASSISTANT</position>
  <contact>JOHN SHARP</contact>
  <email>john@acme.com</email>
  <phone_number>555-555-1212</phone_number>
  <phone_extension>123</phone_extension>
  <contact_current_employer>N</contact_current_employer> Y|N - optional
  <start_date>20000101</start_date> Must be YYYYMMDD
  <end_date>20020101</end_date> Must be YYYYMMDD
  <income>111.00</income>
  <income_type>hourly</income_type> hourly, weekly, monthly, semimonthly,
  biweekly, annually
  <reason_for_leaving>this is an optional field</reason_for_leaving>
  <address1>123 main street</address1>
  <address2></address2>
  <city>AUSTIN</city>
  <state>TX</state> See 'State Conversion'
  <zip>78731</zip>
  <country></country> Not required, normally blank.
  If the value is not blank or "USA", this product is converted to
  International Education/Employment (when it's available in the package)
  ISO 3166-1 Alpha-3 codes preferred;Max 128 chars
  <is_alternate>N</is_alternate> Y|N - optional
  <company_web_address/>
  <supervisor/>
  <supervisor_phone/>
  <comments>Some kind of comment optional</comments>
<question>

```

```

    <prompt>Test Question 1</prompt>
    <standardresponse>Pass</standardresponse>
    <standardresponse>Fail</standardresponse>
  </question>
</question>
  <prompt>Test Question 2</prompt>
  <standardresponse>Yes</standardresponse>
  <standardresponse>No</standardresponse>
</question>
<salarykey>1234</salarykey>
</subOrder>

```

3.8.22 Level2 Employment Verification Order XML

```

<subOrder type='Level2_Employment_verification'>
  <company_name>ABCCO</company_name>
  <position>TEST ASSISTANT</position>
  <contact>JOHN SHARP</contact>
  <email>john@acme.com</email>
  <phone_number>555-555-1212</phone_number>
  <phone_extension>123</phone_extension>
  <contact_current_employer>N</contact_current_employer> Y|N - optional
  <start_date>20000101</start_date> Must be YYYYMMDD
  <end_date>20020101</end_date> Must be YYYYMMDD
  <income>111.00</income>
  <income_type>hourly</income_type>          hourly, weekly, monthly, semimonthly,
                                              biweekly, annually
  <reason_for_leaving>this is an optional field</reason_for_leaving>
  <address1>123 main street</address1>
  <address2></address2>
  <city>AUSTIN</city>
  <state>TX</state>
  <zip>78731</zip>
  <is_alternate>N</is_alternate> Y|N - optional
  <ismilitary/> Y|N - optional
  <company_web_address/>
  <supervisor/>
  <supervisor_phone/>
  <comments>Some kind of comment optional</comments>
  <question>
    <prompt>Test Question 1</prompt>
    <standardresponse>Pass</standardresponse>
    <standardresponse>Fail</standardresponse>
  </question>
  <question>
    <prompt>Test Question 2</prompt>
    <standardresponse>Yes</standardresponse>
    <standardresponse>No</standardresponse>
  </question>
</subOrder>

```

```

</question>
<salarykey>1234</salarykey>
</subOrder>

```

3.8.23 Level3 Employment Verification Order XML

```

<subOrder type='Level3_Employment_verification'>
  <company_name>ABCCO</company_name>
  <position>TEST ASSISTANT</position>
  <contact>JOHN SHARP</contact>
  <email>john@acme.com</email>
  <phone_number>555-555-1212</phone_number>
  <phone_extension>123</phone_extension>
  <contact_current_employer>N</contact_current_employer> Y|N - optional
  <start_date>20000101</start_date> Must be YYYYMMDD
  <end_date>20020101</end_date> Must be YYYYMMDD
  <income>111.00</income>
  <income_type>hourly</income_type>          hourly, weekly, monthly, semimonthly,
                                              biweekly, annually
  <reason_for_leaving>this is an optional field</reason_for_leaving>
  <address1>123 main street</address1>
  <address2></address2>
  <city>AUSTIN</city>
  <state>TX</state>
  <zip>78731</zip>
  <is_alternate>N</is_alternate> Y|N - optional
  <ismilitary/> Y|N - optional
  <company_web_address/>
  <supervisor/>
  <supervisor_phone/>
  <comments>Some kind of comment optional</comments>
  <question>
    <prompt>Test Question 1</prompt>
    <standardresponse>Pass</standardresponse>
    <standardresponse>Fail</standardresponse>
  </question>
  <question>
    <prompt>Test Question 2</prompt>
    <standardresponse>Yes</standardresponse>
    <standardresponse>No</standardresponse>
  </question>
  <salarykey>1234</salarykey>
</subOrder>

```

3.8.24 International Employment Verification Order XML

```

<subOrder type='International_Employment_verification'>
  <company_name>ABCCO</company_name>
  <position>TEST ASSISTANT</position>
  <contact>JOHN SHARP</contact>

```

```

<phone_number>555-555-1212</phone_number>
<phone_extension>123</phone_extension>
<contact_current_employer>N</contact_current_employer> Y|N - optional
<start_date>20000101</start_date> Must be YYYYMMDD
<end_date>20020101</end_date> Must be YYYYMMDD
<income>111.00</income>
<income_type>hourly</income_type>          hourly, weekly, monthly, semimonthly,
                                             biweekly, annually
<reason_for_leaving>this is an optional field</reason_for_leaving>
<address1>38 Holywell St</address1>
<address2></address2>
<city>Oxford</city>
<intlstate>Oxford</intlstate>
<intlzip>OX1 3SP</intlzip>
<country>UK</country> ISO 3166-1 Alpha-3 codes preferred; Max 128 chars
<is_alterate>N</is_alterate> Y|N - optional
<comments>Some kind of comment optional</comments>
<question>
  <prompt>Test Question 1</prompt>
  <standardresponse>Pass</standardresponse>
  <standardresponse>Fail</standardresponse>
</question>
<question>
  <prompt>Test Question 2</prompt>
  <standardresponse>Yes</standardresponse>
  <standardresponse>No</standardresponse>
</question>
<salarykey>1234</salarykey>
</subOrder>

```

3.8.25 I-9 Order XML

```

<Accio_Order>
  <mode>PROD</mode>
  <login>
    <account>account</account>
    <username>admin</username>
    <password>passwd</password>
  </login>
  <placeOrder>
    <SuppressDraftEmailNotice/>
    <NoAdditionalXMLDirectives/>
    <orderInfo>
      <requester_name use_default="Y"/>
      <requester_phone use_default="Y"/>
      <requester_billingdata/>
    </orderInfo>
  </placeOrder>
</Accio_Order>

```

```

<subject>
  <name_last>Smith</name_last>
  <name_first>John</name_first>
  <email>John.Smith@DOMAIN.COM</email>
</subject>

<package>I9 hiddenpackage</package>

  <subOrder type="i9documentation" />
</placeOrder>
</Accio_Order>

```

3.8.26 EVerify Order XML

```

<subOrder type='Everify'>
  <hire_date>20081011</hire_date> Must be YYYYMMDD
  <overdue_reason>1</overdue_reason> See Below
  <overdue_reason_other/>
  <doc_type>28</doc_type> See Below
  <doc_id>25</doc_id>
  <listb_id>101</listb_id> See Below
  <dmv_id_doc_number>M100000111110</dmv_id_doc_number>
  <dmv_id_has_expiration>Y</dmv_id_has_expiration>
  <state_issuing_authority>IL</state_issuing_authority>
  <listc_id>1300</listc_id> See Below
  <doc_exp_date>20160202</doc_exp_date> Must be YYYYMMDD
  <alien_number>678510785</alien_number>
  <i94number>3467925378</i94number>
  <cardnumber>AAA1234567890</cardnumber>
  <visanumber>76098654</visanumber>
  <passportnumber>123456789</passportnumber>
  <supportingdoc_id>1</supportingdoc_id>
  <no_foreign_passport>N</no_foreign_passport>
  <country_issued_code>N/A</country_issued_code> ISO 3166-1 Alpha-3 codes preferred;
  Max 20 chars
</subOrder>

```

The doc.type element can be one of the following:

- 11
- 12
- 13
- 17
- 19
- 24
- 25
- I-94
- I-551

- I-766
- LISTB,CDOCUMENTS
- UNEXPIREDOEXPIREU.S.PASSPORT
- UNEXPIREDFOREIGNPASSPORTWITHI-94STAMP
- UNEXPIREDFOREIGNPASSPORTWITHI-551STAMP

The overdue_reason element can be:

- 1 - Audit revealed that new hire was not run
- 2 - Awaiting social security number
- 3 - Federal contractor verifying an existing employee
- 4 - Other
- 5 - Technical problems

Citizenship Status Codes:

- 4 - A citizen of the United States
- 5 - A noncitizen national of the United States
- 6 - A lawful permanent resident
- 7 - An alien authorized to work

LIST B Document ID's

Citizen Status	Document ID	Document Type
4	1	Driver's license or ID card issued by a U.S. state or outlying possession
4	2	ID card issued by a U.S. federal, state or local government agency
4	3	School ID card
4	4	Voter registration card
4	5	U.S. military card or draft record
4	6	Military dependent's ID card
4	7	U.S. Coast Guard Merchant Mariner Card
4	9	Driver's license issued by a Canadian government authority
4	10	School record or report card (under age 18)
4	11	Clinic, doctor or hospital record (under age 18)
4	12	Day-care or nursery school record (under age 18)
4	8	Native American tribal document
4	21	Minor under age 18 without a List B document
4	22	Special Placement
5	1	Driver's license or ID card issued by a U.S. state or outlying possession
5	2	ID card issued by a U.S. federal, state or local government agency
5	3	School ID card
5	4	Voter registration card
5	5	U.S. military card or draft record
5	6	Military dependent's ID card
5	7	U.S. Coast Guard Merchant Mariner Card

Continued on next page

Citizen Status	Document ID	Document Type
5	9	Driver's license issued by a Canadian government authority
5	10	School record or report card (under age 18)
5	11	Clinic, doctor or hospital record (under age 18)
5	12	Day-care or nursery school record (under age 18)
5	8	Native American tribal document
5	21	Minor under age 18 without a List B document
5	22	Special Placement
6	1	Driver's license or ID card issued by a U.S. state or outlying possession
6	2	ID card issued by a U.S. federal, state or local government agency
6	3	School ID card
6	4	Voter registration card
6	5	U.S. military card or draft record
6	6	Military dependent's ID card
6	7	U.S. Coast Guard Merchant Mariner Card
6	9	Driver's license issued by a Canadian government authority
6	10	School record or report card (under age 18)
6	11	Clinic, doctor or hospital record (under age 18)
6	12	Day-care or nursery school record (under age 18)
6	8	Native American tribal document
6	21	Minor under age 18 without a List B document
6	22	Special Placement
7	1	Driver's license or ID card issued by a U.S. state or outlying possession
7	2	ID card issued by a U.S. federal, state or local government agency
7	3	School ID card
7	4	Voter registration card
7	5	U.S. military card or draft record
7	6	Military dependent's ID card
7	7	U.S. Coast Guard Merchant Mariner Card
7	9	Driver's license issued by a Canadian government authority
7	10	School record or report card (under age 18)
7	11	Clinic, doctor or hospital record (under age 18)
7	12	Day-care or nursery school record (under age 18)
7	8	Native American tribal document
7	21	Minor under age 18 without a List B document
7	22	Special Placement

LIST C Document ID's

Citizen Status	Document ID	Document Type
4	13	Social Security Card
4	14	Certification of Birth Abroad (Form FS-545)
4	15	Certification of Report of Birth (Form DS-1350)
4	23	Consular Report of Birth Abroad (Form FS-240)

Continued on next page

Citizen Status	Document ID	Document Type
4	16	U.S. birth certificate (original or certified copy)
4	17	Native American tribal document
4	18	U.S. Citizen ID Card (Form I-197)
4	19	ID Card for Use of Resident Citizen in the United States (Form I-179)
4	20	Employment authorization document issued by the U.S. Department of Homeland Security
5	13	Social Security Card
5	14	Certification of Birth Abroad (Form FS-545)
5	15	Certification of Report of Birth (Form DS-1350)
5	23	Consular Report of Birth Abroad (Form FS-240)
5	16	U.S. birth certificate (original or certified copy)
5	17	Native American tribal document
5	18	U.S. Citizen ID Card (Form I-197)
5	19	ID Card for Use of Resident Citizen in the United States (Form I-179)
5	20	Employment authorization document issued by the U.S. Department of Homeland Security
6	13	Social Security Card
6	17	Native American tribal document
6	20	Employment authorization document issued by the U.S. Department of Homeland Security
7	13	Social Security Card
7	17	Native American tribal document
7	20	Employment authorization document issued by the U.S. Department of Homeland Security

Other elements are free-form unless otherwise specified

3.8.27 Evictions Check Order XML

```
<subOrder type='evictions_check'>
  <state>TX</state>
</subOrder>
```

3.8.28 FMCSA Crash Inspection Order XML

```
<subOrder type='fmcsa_crash_inspection'>
  <dlnum>22222222</dlnum>
  <dlstate>TX</dlstate>
</subOrder>
```

3.8.29 Gap Verification Order XML

```
<subOrder type='GAP'>
  <start_date></start_date>Must be YYYYMMDD
  <end_date></end_date> Must be YYYYMMDD
  <reference_name>John Smith</reference_name>
  <reference_type>Neighbor</reference_type>
  <reference_phonenumber>555-555-1212</reference_phonenumber>
```

```

    <question>
      <prompt>Test Question 1</prompt>
      <standardresponse>Pass</standardresponse>
      <standardresponse>Fail</standardresponse>
    </question>
    <question>
      <prompt>Test Question 2</prompt>
      <standardresponse>Yes</standardresponse>
      <standardresponse>No</standardresponse>
    </question>
  </subOrder>

```

3.8.30 Medical Sanctions History Order XML (Level 3)

```

<subOrder type='FACIS'>
</subOrder>

```

3.8.31 Medical Sanctions History Order XML (Level 3 - with verification)

Verification request settings are set explicitly by request type

```

<subOrder type='FACIS.L3V'>
</subOrder>

```

3.8.32 Medical Sanctions History Order XML (Level 1)

```

<subOrder type='FACIS.L1'>
</subOrder>

```

3.8.33 Medical Sanctions History Order XML (Level 1 - with verification)

Verification request settings are set explicitly by request type

```

<subOrder type='FACIS.L1V'>
</subOrder>

```

3.8.34 Medical Sanctions History Order XML (Level 1m)

```

<subOrder type='FACIS.L1m'>
</subOrder>

```

3.8.35 Medical Sanctions History Order XML (Level 1m - with verification)

Verification request settings are set explicitly by request type

```

<subOrder type='FACIS.L1mV'>
</subOrder>

```

3.8.36 Medical Sanctions History Order XML (Level 2)

```

<subOrder type='FACIS.L2'>
  <state>TX</state>
</subOrder>

```

3.8.37 Medical Sanctions History Order XML (Level 2 - with verification)

Verification request settings are set explicitly by request type

```
<subOrder type='FACIS.L2V'>
  <state>TX</state>
</subOrder>
```

3.8.38 Office of Foreign Assets Control Search

Note: OFAC is no longer supported and has been replaced by SDN.

3.8.39 Federal Bankruptcy Court Order XML

```
<subOrder type='Federal.criminal.bankruptcy'>
  <county>NORTHERN</county> See info in the Federal Criminal section
  <state>TX</state>
</subOrder>
```

3.8.40 Federal Civil Court Order XML

```
<subOrder type='Federal.criminal.civil'>
  <county>FEDERAL</county> See info in the Federal Criminal section
  <state>AK</state>
  <notes_to_supplier>Please search</notes_to_supplier> optional,
  free-form,
  65000 char limit
</subOrder>
```

3.8.41 Federal Criminal Court Order XML

```
<subOrder type='Federal.criminal.criminal'>
  <county>Travis</county> See notes below
  <state>TX</state>
  <notes_to_supplier>Please search</notes_to_supplier> optional,
  free-form,
  65000 char limit
</subOrder>
```

For District-level Federal searches, Accio Data users will, by default, send the district name, which will be one of CENTRAL, EASTERN, MIDDLE, NORTHERN, SOUTHERN, WESTERN, or FEDERAL (for states with just one district). However, some Accio Data users will choose to send the county name instead, either should be considered valid.

3.8.42 Federal Statewide Bankruptcy Court Order XML

```
<subOrder type='Federal.statewide.bankruptcy'>
  <state>TX</state>
  <years_conviction>7</years_conviction> optional
  <years_nonconviction>7</years_nonconviction> optional
</subOrder>
```

3.8.43 Federal Statewide Civil Court Order XML

```
<subOrder type='Federal.statewide.civil'>
  <state>TX</state>
```

```

<years_conviction>7</years_conviction> optional
<years_nonconviction>7</years_nonconviction> optional
<notes_to_supplier>Please search</notes_to_supplier> optional,
                                                    free-form,
                                                    65000 char limit
</subOrder>

```

3.8.44 Federal Criminal Statewide Court Order XML

```

<subOrder type='Federal_statewide_criminal'>
  <state>TX</state>
  <years_conviction>7</years_conviction> optional
  <years_nonconviction>7</years_nonconviction> optional
  <notes_to_supplier>Please search</notes_to_supplier> optional,
                                                    free-form,
                                                    65000 char limit
</subOrder>

```

3.8.45 General Sanctions Administration List Check Order XML

```

<subOrder type='GSA'>
</subOrder>

```

3.8.46 Global Terrorist Watch List

```

<subOrder type='globalreport'>
</subOrder>

```

3.8.47 Form I-9 Verification Order XML

```

<subOrder type='i9verification'>
  <citizenship_status></citizenship_status>
</subOrder>

```

3.8.48 Mail Completed Report Order XML

```

<subOrder type='mail_complereport'>
</subOrder>

```

3.8.49 Monitor National (Multijurisdictional) Criminal Report Order XML

```

<subOrder type='monitor_national_criminal'>
</subOrder>

```

3.8.50 MVR Order XML

```

<subOrder type='MVR'>
  <dlnum>99990000</dlnum>
  <dlstate>TX</dlstate> See 'State Conversion'
  <mvr_searchtype>standard</mvr_searchtype> Optional
</subOrder>

```

Note that in the absence of a valid value for `mvr_searchtype`, the value “standard” is assumed unless an option selector system variable exists for the state. In this case, the first `mvr` search type specified in the `mvr` option selector, overrides “standard” as the default. Set or check `mvr` option selectors in the “MVR setup” section of the “Operations/site customization” → “Site Setup” page. Valid values for `mvr_searchtype` are:

- standard
- extended
- unlimited
- commercial-use
- cdl

while all states support the ordering of the standard MVR search type, availability of other search types will vary by state depending upon what is offered through the state and/or your vendor.

3.8.51 National (Multijurisdictional) Criminal Report Order XML

```
<subOrder type='National Criminal'>
</subOrder>
```

```
<subOrder type='National Criminal2'>
</subOrder>
```

3.8.52 National Federal Criminal Report Order XML

```
<subOrder type='National Federal Criminal'>
</subOrder>
```

3.8.53 National (Multijurisdictional) Criminal with Alias Report Order XML

```
<subOrder type='National Alias Criminal'>
</subOrder>
```

3.8.54 National (Multijurisdictional) Criminal with Alias Report source 2 Order XML

```
<subOrder type='National Alias Criminal2'>
</subOrder>
```

3.8.55 Nursing License Order XML

```
<subOrder type='nursing_license'>
  <state>TX</state>
  <license_number>12345678</license_number>
</subOrder>
```

3.8.56 Office of Inspector General List Check Order XML

```
<subOrder type='OIG'>
</subOrder>
```

3.8.57 Professional Reference Check Order XML

```
<subOrder type='ProfessionalReference_check'>
  <contactname>John Smith</contactname>
  <contactphone>555-555-1212</contactphone>
  <contactemail>John.Smith@abc.com</contactemail>
  <contactaddress>123 main street</contactaddress>
  <contactcity>AUSTIN</contactcity>
  <contactstate>TX</contactstate>
  <contactzip>78731</contactzip>
```

not required

```

<contactcountry></contactcountry> not required, normally blank
    If the value is not blank or "USA", this product is converted to
    International Education/Employment (when it's available in the package)
    ISO 3166-1 Alpha-3 codes preferred; Max 128 chars
<question>
  <prompt>Test Question 1</prompt>
  <standardresponse>Pass</standardresponse>
  <standardresponse>Fail</standardresponse>
</question>
<question>
  <prompt>Test Question 2</prompt>
  <standardresponse>Yes</standardresponse>
  <standardresponse>No</standardresponse>
</question>
</subOrder>

```

3.8.58 International Professional Reference Check Order XML

```

<subOrder type='InternationalProfessionalReference_check'>
  <contactname>Juan Gonzalez</contactname>
  <contactphone>011-555-555-1212</contactphone>
  <contactemail>Juan.gonzalez@abc.com</contactemail> not required
  <contactaddress>555 de Mayo</contactaddress>
  <contactcity>Ciudad Frontera</contactcity>
  <contactstate>CO</contactstate>
  <contactzip>25668</contactzip>
  <contactcountry>MEX</contactcountry>
  <question>
    <prompt>Test Question 1</prompt>
    <standardresponse>Pass</standardresponse>
    <standardresponse>Fail</standardresponse>
  </question>
  <question>
    <prompt>Test Question 2</prompt>
    <standardresponse>Yes</standardresponse>
    <standardresponse>No</standardresponse>
  </question>
</subOrder>

```

3.8.59 Reference Check Order XML

```

<subOrder type='Reference_check'>
  <contactname>John Smith</contactname>
  <contactphone>555-555-1212</contactphone>
  <contactemail>John.Smith@abc.com</contactemail> not required
  <contactfax>555-555-1212</contactfax> not required
  <type>Personal, Professional, etc</type> not required
  <relationship>coach, supervisor, friend, etc</relationship> not required
  <contactaddress>123 main street</contactaddress>
  <contactcity>AUSTIN</contactcity>

```

```

<contactstate>TX</contactstate>
<contactzip>78731</contactzip>
<comments>Some kind of comment optional</comments>
<question>
  <prompt>Test Question 1</prompt>
  <standardresponse>Pass</standardresponse>
  <standardresponse>Fail</standardresponse>
</question>
<question>
  <prompt>Test Question 2</prompt>
  <standardresponse>Yes</standardresponse>
  <standardresponse>No</standardresponse>
</question>
</subOrder>

```

3.8.60 Safety First Order XML

```

<subOrder type='safety1st'>
</subOrder>

```

3.8.61 Sex Offender Database Order XML

```

<subOrder type='Sex_Offender'>
  <state>TX</state>
</subOrder>

```

3.8.62 Sex Offender Multistate Database Order XML

```

<subOrder type='sex_offender_nationwide'>
</subOrder>

```

3.8.63 Specially Designated Nationals Database Search Order XML

```

<subOrder type='SDN'>
</subOrder>

```

3.8.64 SSN Verification Order XML

```

<subOrder type='SSN'>
</subOrder>

```

3.8.65 Standard Credit Report Order XML

```

<subOrder type='Credit_std'>
</subOrder>

```

3.8.66 Statewide Civil Order XML

```

<subOrder type='Statewide_civil'>
  <state>TX</state>
</subOrder>

```

3.8.67 Statewide Criminal Order XML

```

<subOrder type='Statewide_criminal'>
  <state>TX</state>

```

```

    <notes_to_supplier>Provide Docket Copies for Felonies</notes_to_supplier>optional,
                                                                    free-form,
                                                                    65000 char limit
  </subOrder>

```

3.8.68 Statewide Criminal Data Base Order XML

```

<subOrder type='Statewide_criminal_db'>
  <state>TX</state>
</subOrder>

```

3.8.69 Trac Order XML

```

<subOrder type='Trac'>
</subOrder>

```

3.8.70 Trac_to_7year_criminal Order XML

```

<subOrder type='Trac_to_7year_criminal'>
</subOrder>

```

3.8.71 Trac_to_3year_criminal Order XML

```

<subOrder type='Trac_to_3year_criminal'>
</subOrder>

```

3.8.72 Trac_to_Federal_criminal Order XML

```

<subOrder type='Trac_to_Federal_criminal'>
</subOrder>

```

3.8.73 TriMerged Credit Report Order XML

```

<subOrder type='Credit_tri'>
</subOrder>

```

3.8.74 Workers Compensation Order XML

```

<subOrder type='Workers Compensation'>
  <state>AL</state>
</subOrder>

```

3.9 The addToOrder Block

```

<addToOrder orderID=''12345''> Must match an existing order number in the system
  <account>accountname</account> optional. Used if placing orders on
  <username>username</username> behalf of another user
  <subject>...</subject> not required for addToOrder
  <subOrder type='County_criminal'> ... </subOrder> any number >=1 may be included
  <image/> zero to many images per order
</addToOrder>

```

addToOrder adds additional research items to an existing order. Otherwise, features and restrictions are similar to the placeOrder block.

NOTE : If the optional <subject> node is left off, the subject data from the existing order will be copied to the new subOrder. If the subject node is included in the addToOrder, none of the subject information from the existing order will be copied to the new subOrder.

3.10 Autogenerating Criminal Searches

When placing an order, you can provide a list of addresses in the subject XML in <prioraddress> blocks. If you do so, you may ask the system to automatically generate criminal records searches in the areas indicated by these addresses by adding optional nodes to the <placeOrder> block as outlined below. The system will not order duplicate searches if they appear in the address list more than once or if they have already been ordered elsewhere with subOrder nodes.



Autogenerated criminals will generate only up to the maximum number of searches allowed by the package you're ordering in. Searches beyond the package limit will not be generated.

Tag Name	Function
GenerateCrimsFromSubjectAddresses	<p>Create county criminal searches from each address supplied in <prioraddress> blocks (unless overridden with a statewide search). If a county name is supplied, it is used for the search. If one is not supplied, the system attempts to determine a county to search based on the zip code, if no zip code then city and state is used.</p> <p>If your pricebook is configured to run statewide criminals in certain states in lieu of county courthouse searches, this tag will add a single statewide search in lieu of the county searches it would otherwise have ordered.</p> <p>Your system provider will have configured the statewide overrides for your pricebook by setting the system variable <code>generate_statewide_criminal_states/pricebookname</code>.</p>
GenerateCrimsFromAIMAddresses	<p>As GenerateCrimsFromSubjectAddresses except it adds crims from counties found in the AIM search with this order. If this node is specified but no AIM component was ordered, an error response will be generated.</p>

3.11 Order Control Settings

The following XML elements can be included in your <placeOrder> block to control the ordering process :

Tag Name	Function
<Cancel_out_of_scope_elements>	<p>If your order has elements that are not included in the scope of the package you have ordered or in jurisdictions not allowed, cancel the out of scope elements and order the rest of the elements instead of canceling the entire order.</p> <p>Components that are canceled may have a special status indicator on the response node similar to this : <subOrder type="County_criminal" suborderID="617341" status="canceled - out of scope"/></p> <p>Whether they have this node depends on whether it's an item that is allowed in a package but the package maximum has been exceeded (you'll always get this node) and on whether you've also included the node <Delete_disallowed_products/>. Without the latter, you'll be notified of elements canceled because that product type isn't allowed in your package. With the latter, you will instead be notified of elements deleted because that product type isn't allowed in your package.</p> <p>If the product is in a jurisdiction not allowed, you'll see something like this : <subOrder type="County_criminal" suborderID="617341" status="canceled - jurisdiction not allowed"/></p>
<Delete_disallowed_products>	<p>This node is only used in conjunction with <Cancel_out_of_scope_elements/>. See the documentation for this node above for further information.</p>
<Add_AKAs_from_AIM>	<p>If this node is present, add all AKAs found from the AIM search to this order. Note that if no AIM search is run with this order, inclusion of this element will cause an error to be thrown. This functionality can be modified with the subnode <MaxTotalAKAs> which will set the maximum number of AKAs to add to this order. If MaxTotalAKAs is not specified, then your account's standard setting (the setting that would be used if you placed an order online) will be used. Example:</p> <pre data-bbox="699 1472 1557 1682"> <Add_AKAs_from_AIM/> # Add AKAs from AIM up to the # standard # akas to automatically # include for this account <Add_AKAs_from_AIM> <MaxTotalAKAs>10</MaxTotalAKAs> </Add_AKAs_from_AIM> </pre>

Continued on next page

Order Control Tags (continued)

Tag Name	Function
	<p>NOTE : When specified, the AIM search is run while the connection is held open and the success/failure status messages will be returned only after the AIM search has completed. This will significantly increase the time to submit an order. If you are sending a large number of orders with this setting, you may want to consider parallelizing order submission to us – but please limit parallel connections to 8 at a time.</p> <p>NOTE : If the aforementioned AIM search fails to complete in the timeout interval (100 seconds), this function will not be performed and you will receive an error response with error=52.</p>
<Expand_AKAs_to_Suborders>	<p>When specified, components that are expandable to AKA's (contact us for a list), such as county courthouse searches, will be expanded for all AKA's listed in the original order. AKA's from the AIM search will also be expanded if <Add_AKAs_from_AIM> is specified. This directive only is active when the XML mode is "PROD".</p>
<Upgrade_products_per_package>	<p>When specified, the system will automatically upgrade employment verifications to level 2 employments then to level 3 employments then to CDL employments as necessary to fit the specified package. Reference checks will be upgraded to Professional reference checks as necessary to fit the package. This allows the developer to always send over a standard employment verification (for example) without knowing whether the package ordered instead will run a level 2 or 3 employment. Our software will upgrade the verification as necessary to fit within the products allowed in the package chosen.</p> <p>Any products so upgraded will be shown as the new product type in the XML response document you receive in the "type" attribute, and a new attribute named "origtype" will show the type as originally ordered. When logged on our internal software's XML log we'll see an "origtype" property indicating the original component type as well.</p>

Continued on next page

Order Control Tags (continued)

Tag Name	Function
<UseOrderingRequirements>	When specified, PROD mode XML orders must follow the ordering requirements which are set for the standard order form page. This only checks to see if a value is present for the required field, it does NOT validate if the value present is a valid string or integer for that field, only that a value is present.
<IncludeDefaultProducts>	When specified, default products included in the package will be automatically added to the order even if subOrder nodes are not included for them. This will only work for products that require no additional information to order. E.G. a Credit report could be added, but an employment verification could not. The exceptions are statewide and county criminal searches which are in a package that includes specific state and/or county searches. The statewide searches must have the included=1 and the state defined. The countywide searches must have included=1 the state and county defined.
<IncludePreselectedProducts>	When specified, products preselected in the package will be automatically added to the order even if subOrder nodes are not included for them. This will only work for products that require no additional information to order. E.G. a Credit report could be added, but an employment verification could not.
<preselect_all_included_products>	When specified, products preselected or included in the package will be automatically selected even if subOrder nodes are not included for them (your CRA preselects products on their web-based pricing management interface in the num_preselected column). This directive works for all products regardless of whether they require additional information. Because of this, this node should only be used for draft orders. If this node is used for production orders, products that require additional information (like employment verifications) will be ordered even though they have no information.

Continued on next page

Order Control Tags (continued)

Tag Name	Function
<SuppressApplicantPortalEmail>	When specified, will suppress any email which would have been sent to the applicant to either supply PII, Electronic Wet Signature, or complete the order by the applicant portal.
<SuppressDraftEmailNotice>	When specified, will suppress any email which would have been sent when a DRAFT XML order was entered into the system controlled by the "XML draft order email notification template". This only applies to DRAFT XML orders.
<replace_duplicate_jurisdictions_with_original>	When specified, any other suborders associated with the new order will be searched and duplicate county and statewide criminal searches will be removed from the new search. The results for any suborder removed as a result of this will contain information indicating that the component was deleted and what suborder caused the component to be deleted.
<SendApplicantInviteViaBoth>	Highest Priority (Precedence). This tag is optional if <portalfromapplicant>, <piifromapplicant>, or <require_ews> tags are used. SendApplicantInviteViaBoth will send the applicant invite by both email and SMS.
<SendApplicantInviteViaSMS>	Priority is lower than SendApplicantInviteViaBoth but higher than SendApplicantInviteViaEmail. This tag is optional if <portalfromapplicant>, <piifromapplicant>, or <require_ews> tags is used to send applicant invite over SMS.
<SendApplicantInviteViaEmail>	Lowest Priority (Precedence), This tag is optional if <portalfromapplicant>, <piifromapplicant>, or <require_ews>tags is used to send applicant invite over email.

3.12 The resultsForwarded Block

The resultsForwarded block is an optional block which contains vendor forwarded results. Vendor forwarded results will only appear if

- the option "Receive forwarded results in order" is set to Yes for this vendor
- this order is a vendor forwarded order

The resultsForwarded block contains the results of the component found in the <suborder> ... </suborder> from the previous vendor.

```
<resultsForwarded order="" subOrder="" remote_order="419444" remote_subOrder="1795359"
    held_for_review="N" held_for_release_form="N"
    filledStatus="in progress" filledCode="hits" type="The request Type">
  See the subOrder block in the "XML Results Delivery" manual.
</resultsForwarded>
```

Chapter 4

Order Response

After submitting your order XML, the system will respond in the same session with a response XML document. The response document has the following structure :

```
<XML>
  <order orderID='123456' number='123'>  number is optional, present if specified by you
                                         when ordered
    <subOrder type='sometype' suborderID='654321'>

    </subOrder>
    <applicantPortalURL>
      https://someURL/c/p/collect_information?guikey=epZ5d1Dmbf4uh2ErPZvuiSjSchoanWji
    </applicantPortalURL> optional, present if <piifromapplicant> or <portalfromapplicant>
                           or <require_ews> was set to Y by you when ordered
  </order>
  <error n='12'>  if no errors, none will be present.
    <errortext>some error description related to N in error</errortext>
    <additionalinfo>more information, may not be present</additionalinfo>
  </error>
</XML>
```

4.1 Response Error Codes

- 0 – Unknown error classification
- 1 – XML document was not parseable.
- 2 – Content-Type was not specified.
- 3 – Content-Length was not specified.
- 4 – Content-Type was not text/xml.
- 5 – This shouldn't happen. Please contact customer service for assistance.
- 6 – No login block was included in the XML document posted.
- 7 – No account was specified in the login block.
- 8 – No username was specified in the login block.
- 9 – No password was specified in the login block.

- **10** – Login Authentication for this account failed.
- **11** – This user’s password has expired.
- **12** – Logins for this user have been disabled.
- **13** – Login has been attempted with a temporary password. Only permanent passwords may access the XML research system.
- **14** – The XML document posted to us contained none of a postResults node, a getPendingOrders node, a placeOrder node, an addToOrder node, a getPackages node, node, a additionalFees node or a createUser node. You must include one or more.
- **15** – This account is not configured to manage data for any vendors (vendors_we_manage is empty) or there are no placeOrder/addToOrder/additionalFees/createUser nodes in the XML document. One or the other must be true.
- **16** – The getPendingOrders node had no startingOrderNumber subnode (see ”The getPendingOrders block” in the Accio Data ”XML Integration Manual” for more information)
- **17** – Internal assertion error : tabletoxml matched more than one row.
- **18** – A postResults element contained no order attribute
- **19** – A postResults element contained no subOrder attribute
- **20** – A postResults element contained no filledStatus attribute
- **21** – A postResults element contained no filledCode attribute
- **22** – A postResults element’s filledStatus attribute contained an illegal value
- **23** – A postResults element’s filledCode attribute contained an illegal value
- **24** – A postResults element’s order or subOrder number could not be found in our system
- **25** – The order you are posting to is not assigned to a vendorname you manage. Your client should check your account/user’s vendors_we_manage variable and make sure it is correct.
- **26** – This account/username is not allowed to order (ordering_enabled is not Y)
- **27** – This account/username is not a client account. Client accounts may not order (client is not Y)
- **28** – A placeOrder/addToOrder is attempting to place the order on behalf of another user, but this account does not have sysop or parent privileges
- **29** – Ordering on behalf of other accounts is not yet a released feature and is disabled for this account
- **30** – This subOrder’s type attribute is missing or not recognized
- **31** – This order contained no subOrder elements
- **32** – This order contained no subject element
- **33** – Internal error inserting subject information into our database
- **34** – Internal exception of an unknown nature
- **35** – Subject node subtree contained invalid information, database insert failed
- **36** – An invalid date was supplied
- **37** – An image was supplied with no documenttype attribute (or zero length)
- **38** – An image was supplied with no pagerange attribute (or zero length)
- **39** – An image was supplied with no format attribute (or zero length) valid formats are tiff or pdf
- **40** – An image was supplied with an invalid format (only tiff or pdf accepted)
- **41** – An addToOrder was placed but the referenced orderID could not be found in the account
- **42** – Error inserting a criminalcase into our database, either because an improperly formatted field was posted to us or internal error

- **43** – Error inserting a criminalcharge into our database, either because an improperly formatted field was posted to us or internal error
- **44** – Error inserting a criminal sentence into our database, either because an improperly formatted field was posted to us or internal error
- **45** – Invalid package specified (or none was specified and this account has no A La Carte package)
- **46** – An internal error occurred, please contact Accio Data
- **47** – getPackages is inquiring about another account, but this account does not have the required privileges
- **48** – You are trying to order on behalf of a nonexistent account or getPackages is inquiring about a nonexistent account
- **49** – Secondary account specified but user was not. If you have an iaccount¿ override node, you must also specify a iusername¿ override node
- **50** – Feature not available
- **51** – Add_AKAs_from_AIM was specified but no AIM component was ordered in this request
- **52** – Add_AKAs_from_AIM timed out waiting for the AIM search to fill
- **53** – GenerateCrimsFromAIMAddresses was requested but no AIM component was ordered
- **54** –'Unknown node encoding
- **55** – Secondary account node specified but no value for account name
- **56** – Secondary username node specified but no value for username
- **57** – Error inserting a custom question into our database, either because an improperly formatted field was posted to us or internal error
- **58** – An additionalFees is attempting to edit billing, this is only allowed for sysopl2 users and vendors that are allowed to postback fees
- **59** – missing order attribute on additionalFees node
- **60** – Could not find any information on an order number for additionalFees
- **61** – AdditionalFees amount is invalid. Please use only numbers and a period in the total attribute
- **62** – AdditionalFees did not find total attribute for node
- **63** – User creation is not allowed for demo accounts.
- **64** – This account is not allowed to create new users.
- **65** – A systemAdministration is attempted, but this account does not have sysopl2 privileges
- **66** – A systemAdministration/order element contained no order attribute
- **67** – A systemAdministration/order element contained bad order number attribute
- **68** – Error inserting a defendant/plaintiff/prioraddress into our database, either because an improperly formatted field was posted to us or internal error
- **69** – Error inserting a postalAddress into our database, either because an improperly formatted field was posted to us or internal error
- **70** – A logAction is attempted, but this account does not have sysopl2 privileges
- **71** – A placeOrder/addToOrder is attempting to place the order on behalf of another user, but this account does not have parent privileges
- **72** – A subOrder node did not have a type property
- **73** – An invalid doc_type was supplied
- **74** – Error charging credit card
- **75** – Internal assertion error : tabletoxml did not match any row.

- **76** – Invalid citizenship
- **77** – This order has one or more of the following problems :
 - it contains products not included in this package
 - it contains product(s) in quantities greater than allowed by this package
 - it contains products in jurisdictions not allowed in this package

Please correct and resubmit or consider using the `Cancel_out_of_scope_elements` directive.

- **78** – The `placeOrder/unsolicited` account/username is not allowed to order (`ordering_enabled` is not Y)
- **79** – The `placeOrder/addToOrder/unsolicited` is attempting to place the order on behalf of another user, but the user does not exist; check the spelling of the account and username.
- **80** – The `postResults unsolicited` result account node missing or has no value
- **81** – The `postResults unsolicited` result username node missing or has no value
- **82** – The `postResults unsolicited` result must have 1 and only 1 `subOrder`
- **83** – Missing or empty string for `postResults unsolicited` result `subOrder` type
- **84** – Can not generate signature sign on
- **85** – A `generateSignatureLogin` is attempting to login on behalf of another user, but this account does not have parent privileges
- **86** – A `generateSignatureLogin` is attempting to login on behalf of another user, but this account is not a parent of the other user
- **87** – A `generateGUILogin` is attempting to login on behalf of another user, but this account does not have parent privileges
- **88** – A `generateGUILogin` is attempting to login on behalf of another user, but this account is not a parent of the other user
- **89** – A `getOrderResults` is missing a `orderId` attribute or the `orderId` attribute does not have a value
- **90** – A `getOrderResults` `orderId` attribute value is not a valid order number
- **91** – A `getOrderResults` asked for results you can not view
- **92** – An order with a mode other than DRAFT was submitted with the `preselect_all_included_products` directive, which is allowed only for draft orders
- **93** – A `RenewApplicantPortalURL` is attempting to renew a portal URL on behalf of another user, but this account does not have `sysop` or parent privileges
- **94** – The `RenewApplicantPortalURL` is attempting to renew a portal URL on behalf of another user, but the user does not exist; check the spelling of the account and username.
- **95** – A `RenewApplicantPortalURL` was missing the URL node.
- **96** – A `RenewApplicantPortalURL` URL node was missing a value.
- **97** – A `RenewApplicantPortalURL` URL is missing the `guikey` parameter and value.
- **98** – Did not find `RenewApplicantPortalURL` URL in applicant portal list of URLs for this account and username.
- **99** – `RenewApplicantPortalURL` URL already has had a response from applicant.
- **100** – Missing or bad data for a releaseform.
- **101** – Bad order number for a releaseform.
- **102** – Trying to post a releaseform to an order you do not have permission to access.
- **103** – Encountered an unknown error when uploading a release form.
- **104** – The date of birth is not a valid number of years.

- **105** – A picture was supplied with no format attribute (or zero length) valid formats are jpg or png
- **106** – A picture was supplied with an invalid format (only jpg or png accepted)
- **107** – The placeOrder/addToOrder/unsolicited is attempting to request information from the applicant, to do so the subject/email node must contain the subject's email address, but the node was missing or empty.
- **108** – Your account is not properly configured for StayClear monitoring. Please contact customer service for assistance.
- **109** – Internal problem generating the PDF results. Please contact customer service for assistance.
- **110** – The order you are posting to is now managed by another remote order.
- **111** – The order you are posting to is now managed by another vendor.
- **112** – The order you are posting a web verification to is now managed by *vendor name*.
- **113** – Web verification may not update a filled component.
- **114** – Missing required global state organization id
- **115** – Missing required account state organization id
- **116** – Missing required document upload information
- **117** – Too many criminal charges
- **118** – Received results, but could not update order.
- **119** – Encountered search types that are not enabled for this account.
- **120** – GenerateCrimsFromAIMAddresses timed out waiting for the AIM search to fill.
- **121** – Add2crim timed out waiting for the AIM search to fill.
- **122** – Order timed out waiting for the AIM search to fill.
- **123** – Credit limit exceeded
- **124** – The mode tag is missing or the mode value is not valid.
- **130** – terminations is inquiring about another account, but this account does not have the required privileges
- **131** – terminations person not found
- **132** – invalid termination date
- **999** – This feature is not yet supported.

Orders which are not included in the response XML document were not accepted.

Chapter 5

Sending Imaged Documents

Sometimes it is necessary to attach images to background check requests or results. Signed release forms, employment applications, and supporting documentation may be attached to the order or results as images. Each order/results (<placeOrder> or <postResults>) block in the XML document can contain any number of base64 encoded images in separate <image> tags identified by two keys (documenttype and pagerange) provided as attributes of the image tag. Each image uploaded must have a unique combination of these keys.

Documenttype may be an arbitrary string, but there is one special document type of “Release Form” which should be used to designate a generic release form signed by the applicant.

The tag attribute to designate whether this document is visible to clients or not is titled “clientvisible”. Valid values are ‘Y’ and ‘N’. If clientvisible is not used, the default is ‘Y’.

A sample image tag is as follows :

```
<image documenttype='Release Form' pagerange='all' format='tiff' clientvisible='Y'>
... base64 encoded data ...
</image>
```

Or, to upload images in file per page mode :

```
<image documenttype='Employment Application' pagerange='1' format='tiff'>
... base64 encoded data ...
</image>
<image documenttype='Employment Application' pagerange='2' format='tiff'>
... base64 encoded data ...
</image>
<image documenttype='Employment Application' pagerange='3' format='tiff'>
... base64 encoded data ...
</image>
```

5.1 Image File Formats

The uploaded image’s file format is designated in the “format” attribute of the image tag. The only supported formats at this time are tiff and pdf.

Chapter 6

Other XML Queries

6.1 Packages

If desired, XML can be used to pull a list of packages available to an account. Attempting to place an order with an invalid packagename will result in an error message listing the available packages, but this query will return more information about the packages available to you. All you need to do is include a `getPackages` node in your XML request as in the following example :

```
<New_Order>
  <login>
    <account>youraccount</account>
    <username>youruser</username>
    <password>yourpassword</password>
  </login>
  <getPackages account="subaccount"/>
</New_Order>
```

The response document will be as follows :

```
<XML>
  <package>somename</package>
  .
  .
  .
</XML>
```

If the account is a sysop or client user with switch user capabilities, then you can include an account attribute to the `getPackages` node.

6.2 Results for a specific order

Normally order results are pushed when a component completes and/or when the order is completed. If desired you can pull the results for a specific order. All you need to do to get the results for a specific order is put a `getOrderResults` node in your XML request as in the following example :

```
<XML>
  <login>
    <account>youraccount</account>
    <username>youruser</username>
    <password>yourpassword</password>
  </login>
  <getOrderResults orderID="427722" />
</XML>
```

The value of the attribute `orderID` is the order number of the results you wish to pull.

The response document, including additional `getOrderResults` attribute settings, is defined in the Chapter “Results for a specific order” in the Results Delivery manual.

Chapter 7

Standard Data Formats

7.1 Dates

Most dates sent to Accio Data must be formatted in our standard date format, which is YYYYMMDD. Any unknown or unspecified date element will be represented by 00. E.G. 19820300 reads as March ??, 1982.

There are also some special date formats allowed as follows :

- **current** : used in End Date field for present employer
- **99990000** : used in End Date field for present employer, means “current”

This is supported for both standard data entry and applicantcheck/schoolcheck. A current date in numeric representation in the XML interface would be entered as “99990000”.

7.2 Data Definition Guide for Common “<placeOrder >” XML Elements

The following is a list of common XML node elements and their presentation/storage considerations. This list is not all-inclusive but rather a work in progress. Additional elements will be added as required.

7.2.1 Elements of the Subject node

Elements of the “<subject >” node			
XML Element	Display Value	Data Length	Data Format
<name_first>	First Name	50 characters	letters, dashes, and apostrophes only
<name_middle>	Middle Name	50 characters	letters, dashes, and apostrophes only
<name_last>	Last Name	50 characters	letters, dashes, and apostrophes only
<name_lastmaiden>	Maiden Last Name	50 characters	letters, dashes, and apostrophes only
<name_suffix>	Name Suffix	8 characters	free form

Continued on next page

(continued from previous page)

XML Element	Display Value	Data Length	Data Format
<has_no_middle_name>	Has No Middle Name	1 character	Y for yes, N for No, U for unknown anything else you get unexpected results.
<ssn>	Social Security Number	10 characters	integer
<dob>	Date of Birth	10 characters	integer(YYYYMMDD)
<gender>	Gender	1 character	M or F
<race>	Race	50 characters	alphabetic
<phone_number>	Phone Number	50 characters	alphanumeric
<address>	Address	255 characters	alphanumeric
<city>	City	50 characters	alphanumeric
<state>	State	50 characters	alphabetic
<zip>	Postal Zip Code	50 characters	alphanumeric
<manager_name>	Manager Name	64 characters	alphanumeric
<position_requested>	Position Requested	128 characters	alphanumeric
<drugscreen>	Is a Drug Screen	1 character	Y or N
<citizenship_status>	Citizenship Status	128 characters	alphanumeric
<employment_status>	Employment Status	128 characters	alphanumeric
<ApplicantID>	Applicant ID	32 characters	alphanumeric

Note, For the name_first, name_middle, name_last and name_lastmaiden alphanumeric contents are accepted, but if the order goes in in draft mode or requires modification in the Order Entry screen, the user makign the modifications will be forced to use letters and dashes only

7.2.2 Elements of the subOrder node, Education_verification attribute

Elements of the "<subOrder >" node, Education_verification attribute			
XML Element	Display Value	Data Length	Data Format
<name_first>	Name first	128 characters	alphanumeric
<name_last>	Name last	128 characters	alphanumeric
<campus>	Campus	128 characters	alphanumeric
<school_name_>	School name	128 characters	alphanumeric
<school_type_>	School type	128 characters	alphanumeric
<othername>	Other name	128 characters	alphanumeric
<attended_from_>	Attended from	10 characters	integer(YYYYMMDD)
<attended_to_>	Attended to	10 characters	integer(YYYYMMDD)
<major>	Major	64 characters	alphanumeric
<degree>	Degree	32 characters	alphanumeric
<GPA>	Gpa	50 characters	floating point
<graduated>	Graduated	1 character	Y or N
<graduation_date>	Graduation date	10 characters	integer(YYYYMMDD)
<highest_achieved>	Highest achieved	1 character	Y or N
<currently_enrolled>	Currently enrolled	1 character	Y or N
<levelCompleted>	Level completed	32 characters	alphanumeric

Continued on next page

(continued from previous page)

XML Element	Display Value	Data Length	Data Format
<student_id_number>	Student id number	128 characters	alphanumeric
<transcript>	Transcript	1 character	Y or N
<phone>	Phone	128 characters	alphanumeric
<address1>	Address1	128 characters	alphanumeric
<address2>	Address2	128 characters	alphanumeric
<city>	City	128 characters	alphanumeric
<state>	State	128 characters	alphabetic
<country>	Country	128 characters	alphanumeric
<zip>	Zip	10 characters	alphanumeric
<comments>	Comments	16777215 bytes	BLOB

7.2.3 Elements of the subOrder node, Employment verification attribute

Elements of the “<subOrder >” node, Employment verification attribute			
XML Element	Display Value	Data Length	Data Format
<company_name>	Company name	128 characters	alphanumeric
<position>	Position	128 characters	alphanumeric
<contact>	Contact	128 characters	alphanumeric
<supervisor>	Supervisor	128 characters	alphanumeric
<supervisor_phone>	Supervisor phone	256 characters	alphanumeric
<email>	Email	128 characters	alphanumeric
<contact_current_employer>	Contact this employer (whether current or not, current in the node name is a misnomer)	1 character	Y or N
<employeeid>	Employee id	128 characters	alphanumeric
<income>	Income	10 characters	floating point
<income_type>	Income type	20 characters	hourly, weekly, monthly, semimonthly, biweekly, annually
<startincome>	Startincome	128 characters	alphanumeric
<endincome>	Endincome	128 characters	alphanumeric
<salarykey>	Salary key	128 characters	alphanumeric
<start_date_>	Start date	10 characters	integer(YYYYMMDD)
<end_date_>	End date to	10 characters	integer(YYYYMMDD)
<reason_for_leaving>	Reason for leaving	512 characters	alphanumeric
<phone_number>	Phone Number	20 characters	alphanumeric
<phone_extension>	Phone extension	10 characters	alphanumeric
<address1>	Address1	128 characters	alphanumeric
<address2>	Address2	128 characters	alphanumeric

Continued on next page

(continued from previous page)

XML Element	Display Value	Data Length	Data Format
<city>	City	128 characters	alphanumeric
<state>	State	2 characters	alphabetic
<zip>	Zip	10 characters	alphabetic
<is_alternate>	Is alternate	1 character	Y or N
<employercode>	Employer code	128 characters	alphanumeric
<employer_status>	Employer status	1 character	U, P, C, and S ***
<comments>	Comments	16777215 bytes	BLOB

- ***Interpret values as: [U]known, [P]revious, [C]urrent), [S]ame as current.

7.2.4 Elements of the subOrder node, fmcsa_crash_inspection attribute

Elements of the “<subOrder >” node, fmcsa_crash_inspection attribute			
XML Element	Display Value	Data Length	Data Format
<dlnum>	License number	50 characters	alphanumeric state-specific
<state>	License State	2 characters	alphabetic

7.2.5 Elements of the subOrder node, MVR attribute

Elements of the “<subOrder >” node, MVR attribute			
XML Element	Display Value	Data Length	Data Format
<dlnum>	License number	50 characters	alphanumeric state-specific
<state>	License State	2 characters	alphabetic
<mvr_searchtype>	MVR search type	20 characters	standard, extended, etc
<dlexpiration>	License expiration	10 characters	integer(YYYYMMDD)

7.3 State Conversion

The standard format for specifying states of the United States is using the 2 letter state abbreviation. The Accio XML integration will attempt to automatically convert full state names into their 2 letter abbreviation for <subject> and <subOrder> nodes.

Index

A

account, [17](#)
add2crim10yr
 Order XML, [27](#)
add2crim7yr
 Order XML, [27](#)
add2statewidecrim10yr
 Order XML, [28](#)
add2statewidecrim7yr
 Order XML, [27](#)
Add_AKAs_from_AIM, [48](#)
addToOrder, [47](#)
Adult Abuse
 Order XML, [28](#)
Adverse Action Process
 Order XML, [28](#)
AIM
 Order XML, [28](#)

C

Cancel_out_of_scope_elements, [48](#)
CBSV
 Order XML, [28](#)
CDL Employment Verification
 Order XML, [28](#)
CDLIS
 Order XML, [28](#)
Certified Nurses Aid Registry
 Order XML, [30](#)
Civil County Lower
 Order XML, [29](#)
Civil County Upper
 Order XML, [29](#)
County Criminal
 Order XML, [29](#)
Credential Verification
 Order XML, [30](#)
Custom Product
 Order XML, [30](#)

D

Date formats, [63](#)
Drug Screen
 Order XML, [31](#)

E

Education Verification
 Order XML, [31](#)
Employment Credit
 Order XML, [33](#)
Employment Verification
 Order XML, [33](#)
Everify
 Order XML, [37](#)
Evictions Check
 Order XML, [40](#)
Expand_AKAs_to_Suborders, [48](#)

F

FACIS
 Order XML, [41](#)
FACIS_L1
 Order XML, [41](#)
FACIS_L1m
 Order XML, [41](#)
FACIS_L1mV
 Order XML, [41](#)
FACIS_L1V
 Order XML, [41](#)
FACIS_L2
 Order XML, [41](#)
FACIS_L2V
 Order XML, [42](#)
FACIS_L3V
 Order XML, [41](#)
Federal Bankruptcy
 Order XML, [42](#)
Federal Civil
 Order XML, [42](#)
Federal Criminal

Order XML, [42](#)
 Federal Statewide Bankruptcy
 Order XML, [42](#)
 Federal Statewide Civil
 Order XML, [42](#)
 Federal Statewide Criminal
 Order XML, [43](#)
 FMCSA Crash Inspection
 Order XML, [40](#)
 Form I-9 Verification
 Order XML, [43](#)

G

Gap Verification
 Order XML, [40](#)
 GenerateCrimsFromAIMAddresses, [48](#)
 GenerateCrimsFromSubjectAddresses, [48](#)
 Generated Criminal Searches, [48](#)
 globalreport
 Order XML, [43](#)
 GSA
 Order XML, [43](#)

I

I-9
 Order XML, [36](#)
 IncludeDefaultProducts, [51](#)
 IncludePreselectedProducts, [51](#)
 International Education Verification
 Order XML, [32](#)
 International Employment Verification
 Order XML, [35](#)
 International Professional Reference Check
 Order XML, [45](#)

L

Level2 Employment Verification
 Order XML, [34](#)
 Level3 Employment Verification
 Order XML, [35](#)
 login, [17](#)

M

Mail Completed Report
 Order XML, [43](#)
 mode, [17](#)
 Monitor National Criminal
 Order XML, [43](#)

Monitor National Multijurisdictional Criminal
 Order XML, [43](#)
 Multijurisdictional Criminal
 Order XML, [44](#)
 Multijurisdictional Criminal with Alias
 Order XML, [44](#)
 Multijurisdictional Criminal with Alias source 2
 Order XML, [44](#)
 MVR
 Order XML, [43](#)

N

National Alias Criminal
 Order XML, [44](#)
 National Alias Criminal2
 Order XML, [44](#)
 National Criminal
 Order XML, [44](#)
 National Federal Criminal
 Order XML, [44](#)
 Nursing License
 Order XML, [44](#)

O

OFAC
 Order XML, [42](#)
 OIG
 Order XML, [44](#)
 orderInfo, [22](#)
 orderOnBehalfOf, [19](#)

P

package, [18](#), [61](#)
 password, [17](#)
 placeOrder, [18](#)
 postBackInfo, [20](#)
 preselect_all_included_products, [51](#)
 Professional Reference Check
 Order XML, [44](#)

R

Reference Check
 Order XML, [45](#)
 replace_duplicate_jurisdictions_with_original, [52](#)
 resultsForwarded
 Order XML, [52](#)

S

Safety First

Order XML, [46](#)

SDN

Order XML, [46](#)

SendApplicantInviteViaBoth, [52](#)

SendApplicantInviteViaEMail, [52](#)

SendApplicantInviteViaSMS, [52](#)

Sex Offender

Order XML, [46](#)

Sex Offender Multistate

Order XML, [46](#)

specificresults, [61](#)

SSN verification

Order XML, [46](#)

Standard Credit

Order XML, [46](#)

Statewide Civil

Order XML, [46](#)

Statewide Criminal

Order XML, [46](#)

Statewide Criminal Database

Order XML, [47](#)

Subject

Order XML, [22](#)

subOrder, [24](#)

SuppressApplicantPortalEmail, [52](#)

SuppressDraftEmailNotice, [52](#)

T

Trac

Order XML, [47](#)

Trac_to_3year_criminal

Order XML, [47](#)

Trac_to_7year_criminal

Order XML, [47](#)

Trac_to_Federal_criminal

Order XML, [47](#)

TriMerged Credit

Order XML, [47](#)

U

Upgrade_products_per_package, [50](#)

URL, [9](#)

UseOrderingRequirements, [51](#)

username, [17](#)

W

Workers Compensation

Order XML, [47](#)

Revision History

Version number follows this pattern, MAJOR.MINOR.PATCH, where:

1. MAJOR version incremented when incompatible changes are made
2. MINOR version incremented when functionality in a backwards-compatible manner is added
3. PATCH version incremented when backwards-compatible bug fixes are made

Revision History

Revision	Date	Description
1.0.0	01/05/2018	Creation (original)